

SECTION B — PERFORMING OPERATIONS; TRANSPORTING

B60 VEHICLES IN GENERAL

B60B VEHICLE WHEELS (making wheels or wheel parts by rolling B21H 1/00, by forging, hammering or pressing B21K 1/28); CASTORS; AXLES; INCREASING WHEEL ADHESION

Note(s)

Attention is drawn to the Note following the title of class B60.

Subclass index

WHEELS

General structure.....	1/00, 3/00
Characterised by the material.....	5/00
Ornamental characteristics.....	7/00
Particular structures: highly- resilient; multiple or multi-tyred; adhesion-increasing; rail-engaging.....	9/00, 11/00, 15/00, 17/00
Component parts	
spokes; rims.....	1/00, 21/00, 23/00, 25/00
hubs.....	27/00
Other wheels.....	19/00
AXLES; WHEEL-AXLE COMBINATIONS.....	35/00, 37/00
INCREASING WHEEL ADHESION, OTHERWISE THAN BY WHEEL STRUCTURE.....	39/00
MOUNTING, HOLDING OR ASSEMBLING WHEELS.....	29/00, 30/00, 31/00
CASTORS IN GENERAL.....	33/00

Wheels

- 1/00 Spoked wheels; Spokes thereof** (non-metallic B60B 5/00) [2]
- 1/02 • Wheels with wire or other tension spokes
 - 1/04 • • Attaching spokes to rim or hub
 - 1/06 • Wheels with compression spokes (wheels of high resiliency B60B 9/00)
 - 1/08 • • formed by casting
 - 1/10 • • fabricated from sheet metal (B60B 1/12, B60B 3/08 take precedence)
 - 1/12 • • with tubular spokes (B60B 1/08 takes precedence)
 - 1/14 • • Attaching spokes to rim or hub
- 3/00 Disc wheels, i.e. wheels with load-supporting disc body** (non-metallic B60B 5/00; wheel cover discs B60B 7/00)
- 3/02 • with a single disc body integral with rim
 - 3/04 • with a single disc body not integral with rim
 - 3/06 • formed by casting
 - 3/08 • with disc body formed by two or more axially-spaced discs
 - 3/10 • apertured to simulate spoked wheels
 - 3/12 • Means of reinforcing disc bodies
 - 3/14 • Attaching disc body to hub (resiliently B60B 9/00; attaching rim to wheel body B60B 23/00)
 - 3/16 • • by bolts or the like
 - 3/18 • • by circlips or the like

- 5/00 Wheels, spokes, disc bodies, rims, hubs, wholly or predominantly made of non-metallic material** (wheel cover discs B60B 7/00; wheels of high resiliency B60B 9/00)
- 5/02 • made of synthetic material
 - 5/04 • made of wood
- 7/00 Wheel cover discs, rings, or the like, for ornamenting, protecting, or obscuring, wholly or in part, the wheel body, rim, hub, or tyre sidewall** [2, 5]
- 7/01 • Rings specially adapted for covering only the wheel rim or the tyre sidewall, e.g. removable tyre sidewall trim rings [5]
 - 7/02 • made essentially in one part (B60B 7/01 takes precedence) [5]
 - 7/04 • built-up of several main parts (B60B 7/01, B60B 7/20 take precedence) [5]
 - 7/06 • Fastening arrangements therefor (B60B 7/01, B60B 7/16 take precedence) [5]
 - 7/08 • • having gripping elements consisting of formations integral with the cover [5]
 - 7/10 • • comprising a plurality of spaced spring clips individually mounted on the cover, e.g. riveted, welded or readily releasable [5]
 - 7/12 • • comprising an annular spring or gripping element mounted on the cover (B60B 7/08 takes precedence) [5]
 - 7/14 • • comprising screw-threaded means [5]
 - 7/16 • Anti-theft devices [5]
 - 7/18 • simulating spoked or wire wheel [5]

B60B

- | | |
|--------------|--|
| 7/20 | <ul style="list-style-type: none"> • having an element mounted for rotation independently of wheel rotation [5] |
| 9/00 | Wheels of high resiliency |
| 9/02 | <ul style="list-style-type: none"> • using springs (wheels comprising resilient spokes B60B 9/26) |
| 9/04 | <ul style="list-style-type: none"> • • in leaf form |
| 9/06 | <ul style="list-style-type: none"> • • in helical form |
| 9/08 | <ul style="list-style-type: none"> • • in flat coiled form |
| 9/10 | <ul style="list-style-type: none"> • • of rubber or the like |
| 9/12 | <ul style="list-style-type: none"> • • • in the form of sleeves or rings concentric with wheel axis |
| 9/14 | <ul style="list-style-type: none"> • • • with means limiting relative lateral movements between hub and remainder of wheel |
| 9/16 | <ul style="list-style-type: none"> • • • modified to ensure electric conductivity |
| 9/18 | <ul style="list-style-type: none"> • using fluid (within spokes B60B 9/26) |
| 9/20 | <ul style="list-style-type: none"> • • in rings concentric with wheel axis |
| 9/22 | <ul style="list-style-type: none"> • • • inflatable |
| 9/24 | <ul style="list-style-type: none"> • • with pistons and cylinders |
| 9/26 | <ul style="list-style-type: none"> • comprising resilient spokes |
| 9/28 | <ul style="list-style-type: none"> • • with telescopic action |
| 11/00 | Units comprising multiple wheels arranged side by side; Wheels having more than one rim or capable of carrying more than one tyre |
| 11/02 | <ul style="list-style-type: none"> • Units of separate wheels mounted for independent or coupled rotation |
| 11/04 | <ul style="list-style-type: none"> • Wheels with a rim capable of carrying more than one tyre |
| 11/06 | <ul style="list-style-type: none"> • Wheels with more than one rim mounted on a single wheel body |
| 11/08 | <ul style="list-style-type: none"> • Arrangements of balancing mechanisms enabling a uniform distribution of load to the tyres |
| 11/10 | <ul style="list-style-type: none"> • Emergency wheels (tyres collapsible into storage or non-use condition B60C 3/08; tyres characterised by means enabling restricted operation in damaged or deflated condition B60C 17/00) [5] |
| 15/00 | Wheels or wheel attachments designed for increasing traction (vehicle tyres B60C; non-skid devices temporarily attachable to resilient tyres or resiliently-tyred wheels B60C 27/00) |
| 15/02 | <ul style="list-style-type: none"> • Wheels with spade lugs |
| 15/04 | <ul style="list-style-type: none"> • • with resiliently-mounted spade lugs |
| 15/06 | <ul style="list-style-type: none"> • • with pivotally-mounted spade lugs |
| 15/08 | <ul style="list-style-type: none"> • • with spade lugs axially displaced relatively to the tread surface of the tyre |
| 15/10 | <ul style="list-style-type: none"> • • with radially-adjustable spade lugs; Control mechanisms therefor |
| 15/12 | <ul style="list-style-type: none"> • • • involving cams or eccentric hoops |
| 15/14 | <ul style="list-style-type: none"> • • • involving an axially-displaceable cone |
| 15/16 | <ul style="list-style-type: none"> • • • involving gearing, e.g. gear pinions acting upon threaded shafts on the spade lugs |
| 15/18 | <ul style="list-style-type: none"> • Wheels with ground-engaging plate-like shoes |
| 15/20 | <ul style="list-style-type: none"> • • with resiliently-mounted shoes, e.g. on a spider |
| 15/22 | <ul style="list-style-type: none"> • • connected by links to the hub |
| 15/24 | <ul style="list-style-type: none"> • Tread bands or rings for fairing lugs when travelling on the road |
| 15/26 | <ul style="list-style-type: none"> • Auxiliary wheels or rings with traction-increasing surface attachable to the main wheel body |
| 15/28 | <ul style="list-style-type: none"> • Wheel-ballasting weights; Their attachment |
| 17/00 | Wheels characterised by rail-engaging elements (of model railways A63H 19/22) [2] |
| 17/02 | <ul style="list-style-type: none"> • with elastic tyres |

- | | |
|-------|---|
| 19/00 | Wheels not otherwise provided for or having characteristics specified in one of the subgroups of this group |
| 19/02 | <ul style="list-style-type: none"> • convertible, e.g. from road wheel to rail wheel; Wheels specially designed for alternative use on road and rail |
| 19/04 | <ul style="list-style-type: none"> • expansible |
| 19/06 | <ul style="list-style-type: none"> • with compartments for fluid, packing, or loading material; Buoyant wheels |
| 19/08 | <ul style="list-style-type: none"> • with lubricating passages, channels, or reservoirs |
| 19/10 | <ul style="list-style-type: none"> • with cooling fins |
| 19/12 | <ul style="list-style-type: none"> • Roller-type wheels (B60B 19/06 takes precedence) |
| 19/14 | <ul style="list-style-type: none"> • Ball-type wheels (B60B 19/06 takes precedence) |

Rims; Hubs

- | | |
|-------|---|
| 21/00 | Rims (non-metallic B60B 5/00; of high resiliency B60B 9/00; capable of carrying more than one tyre B60B 11/04; multiple rims on single wheel body B60B 11/06; of multi-part type B60B 25/00; metal tyres B60C) |
| 21/02 | • characterised by transverse section |
| 21/04 | • • with substantially-radial flanges (with rail-engaging flanges B60B 17/00) |
| 21/06 | • characterised by means for attaching spokes |
| 21/08 | • characterised by having braking surfaces |
| 21/10 | • characterised by the form of tyre-seat or flange, e.g. corrugated (B60B 21/02 takes precedence) |
| 21/12 | • Accessories, e.g. lining bands |
| 23/00 | Attaching rim to wheel body (attaching spokes to rim B60B 1/04, B60B 1/14; attaching rims resiliently to wheel body B60B 9/00) |
| | Note(s) |
| | Group B60B 23/12 takes precedence over groups B60B 23/02-B60B 23/06. |
| 23/02 | • by split or other expansible ring devices |
| 23/04 | • by bayonet-joint, screw-thread, or like attachments |
| 23/06 | • by screws, bolts, pins, or clips |
| 23/08 | • • arranged radially |
| 23/10 | • • arranged axially |
| 23/12 | • by devices arranged to permit variation of axial position of rim relative to wheel body for track-width adjustment |
| 25/00 | Rims built-up of several main parts (tools for assembling divided rims B60B 31/04) |
| 25/02 | • Segmented rims, e.g. with segments arranged in sections; Connecting equipment, e.g. hinges; Insertable flange rings therefor |
| 25/04 | • Rims with dismountable flange rings, seat rings, or lock rings |
| 25/06 | • • Split flange rings, e.g. transversely split; Connecting equipment for overlapping the slot |
| 25/08 | • • Continuous flange rings; Arrangement of recesses enabling the flange ring to be slipped over the rim body |
| 25/10 | • • Seat rings for the tyre bead part, e.g. split |
| 25/12 | • • • with integral flange part |
| 25/14 | • • Locking means for flange rings or seat rings |
| 25/16 | • • • Arrangement of bayonet catches |
| 25/18 | • • • Arrangement of split rings |
| 25/20 | • • • Arrangement of screw, bolts, or shouldered pins |
| 25/22 | • Other accessories, e.g. for sealing the component parts enabling the use of tubeless tyres |

27/00 Hubs (non-metallic B60B 5/00; of high resiliency B60B 9/00)

- 27/02 • adapted to be rotatably arranged on axle
- 27/04 • • housing driving means, e.g. sprockets
- 27/06 • adapted to be fixed on axle

Apparatus or tools for mounting, holding or assembling wheels

29/00 Apparatus or tools for mounting or dismounting wheels (characterised by the means for holding the wheels B60B 30/00) [5]

30/00 Means for holding wheels or parts thereof (spare wheel stowing, holding or mounting arrangements on vehicles B62D 43/00) [5]

- 30/02 • engaging the tyre, e.g. the tyre being mounted on the wheel rim [5]
- 30/04 • • the tyre not being mounted on a rim, i.e. holders or supports for tyres alone [5]
- 30/06 • engaging the wheel body, e.g. the rim [5]
- 30/08 • • the central part of the wheel body [5]
- 30/10 • characterised by being provided on a dolly [5]

31/00 Apparatus or tools for assembling or disassembling wheels

- 31/02 • for tightening or straightening wire spokes in situ; for extracting spokes from wheels
- 31/04 • for assembling divided rims
- 31/06 • for removing or attaching cover discs, hub caps, or the like [2]

33/00 Castors in general (castors for large containers B65D 90/18)

- 33/02 • with disengageable swivel action
- 33/04 • adjustable
- 33/06 • • mounted retractably
- 33/08 • Ball castors

35/00 Axle units; Parts thereof (resilient suspension of a rigid axle or axle housing B60G 9/00; steerable vehicle stub-axles B62D)

35/02 • Dead axles, i.e. not transmitting torque (axle housings for torque transmitting elements B60B 35/16)

- 35/04 • • straight
- 35/06 • • cranked
- 35/08 • • of closed hollow section
- 35/10 • • adjustable for varying track
- 35/12 • Torque-transmitting axles
- 35/14 • • composite or split, e.g. half-axles; Couplings between axle parts or sections (B60G 3/24 takes precedence)
- 35/16 • • characterised by the axle housings for the torque transmitting elements, e.g. for shafts
- 35/18 • • characterised by the arrangement of the bearings for the torque transmitting elements in the axle housings

37/00 Wheel-axle combinations, e.g. wheel sets (units comprising multiple wheels arranged side by side B60B 11/00; rail-vehicle axle-boxes B61F)

- 37/02 • the wheels being integral with solid axles
- 37/04 • the wheels being rigidly attached to solid axles
- 37/06 • the wheels being integral with, or rigidly attached to, hollow axles
- 37/08 • • the hollow axles being rotatable around fixed axles
- 37/10 • the wheels being individually rotatable around the axles
- 37/12 • Axles with a fixed wheel and a loose wheel

39/00 Increasing wheel adhesion (wheels or wheel attachments designed for increasing traction B60B 15/00; vehicle tyres B60C; non-skid devices temporarily attachable to resilient tyres or resiliently-tyred wheels B60C 27/00; road surface conditioning to prevent slipperiness E01C)

- 39/02 • Vehicle fittings for scattering or dispensing material in front of its wheels
- 39/04 • • the material being granular, e.g. sand (combined control of sanding apparatus and brakes of rail vehicles B61H)
- 39/06 • • • the dispensing being effected by mechanical means
- 39/08 • • • the dispensing being effected by fluid means
- 39/10 • • • the dispensing being controlled electrically or electromagnetically
- 39/12 • • the material being sheet-like or web-like