

SECTION B — PERFORMING OPERATIONS; TRANSPORTING

B62 LAND VEHICLES FOR TRAVELLING OTHERWISE THAN ON RAILS

B62D MOTOR VEHICLES; TRAILERS (steering, or guiding on a desired track, of agricultural machines or implements A01B 69/00; wheels, castors, axles, increasing wheel adhesion B60B; vehicle tyres, tyre inflation or tyre changing B60C; connections between vehicles of a train or the like B60D; vehicles for use on rail and road, amphibious or convertible vehicles B60F; suspension arrangements B60G; heating, cooling, ventilating or other air treating devices B60H; windows, windscreens, non-fixed roofs, doors or similar devices, protective coverings for vehicles not in use B60J; propulsion plant arrangements, auxiliary drives, transmissions, controls, instrumentation or dashboards B60K; electric equipment or propulsion of electrically-propelled vehicles B60L; power supply for electrically-propelled vehicles B60M; passenger accommodation not otherwise provided for B60N; adaptations for load transportation or to carry special loads or objects B60P; arrangement of signalling or lighting devices, the mounting or supporting thereof or circuits therefor, for vehicles in general B60Q; vehicles, vehicle fittings or vehicle parts, not otherwise provided for B60R; servicing, cleaning, repairing, supporting, lifting, or manoeuvring, not otherwise provided for B60S; brake arrangements, brake control systems or parts thereof B60T; air-cushion vehicles B60V; motorcycles, accessories therefor B62J, B62K; testing of vehicles G01M)

Note(s)

In this subclass, the following terms are used with the meanings indicated:

- "vehicles" includes motor vehicles and trailers;
- "trailers" includes forecars or sidecars.

Subclass index

FUNCTIONAL OR STRUCTURAL CHARACTERISTICS; PARTS OR ACCESSORIES THEREOF NOT OTHERWISE PROVIDED FOR

Predominantly for passengers; load carrying.....	31/00, 47/00, 33/00
Tractors; tractor-trailer combinations or road trains; vehicles with no seat for the driver.....	49/00, 53/00, 51/00
Endless-track vehicles and their tracks; vehicles with ground engagement other than by tracks or wheels.....	55/00, 57/00
Trailers with driven ground wheels; Motor vehicles or trailers, characterised by the arrangement or number of wheels.....	59/00, 61/00
Other types of vehicles; designing, manufacturing, assembling, disassembling of vehicles.....	63/00, 65/00, 67/00
CHASSIS FRAME, SUPERSTRUCTURE, AND BODY	
Chassis frame; monocoque construction; connections between body and frame.....	21/00, 23/00, 24/00
Superstructure and body characterised	
by material.....	29/00
the function of the vehicle.....	31/00, 33/00
streamlining; stabilising.....	35/00, 37/00, 17/00
superstructure sub-units and connections thereof; arrangements for spare wheel.....	25/00, 27/00, 43/00
radius rods.....	19/00
other vehicle bodies.....	39/00

STEERING

Initiating means; gears; response to driving conditions; linkage; adjusting.....	1/00, 3/00, 6/00, 7/00, 17/00
Power-assisted; automatically influencing; for endless-track vehicles; for trailers.....	5/00, 6/00, 11/00, 13/00
Tandem vehicles or pivotally connected frames.....	12/00
Other.....	9/00, 11/00, 15/00
ACCESSORIES FOR COLLISION MARKING.....	41/00

Steering of motor vehicles or trailers [3]

- 1/00 Steering controls, i.e. means for initiating a change of direction of the vehicle [4, 5]**
- 1/02 • vehicle-mounted
- 1/04 • • Hand wheels

- 1/06 • • • Rims, e.g. with heating means; Rim covers (B62D 1/11 takes precedence) [5]
- 1/08 • • • Spokes, e.g. resilient (B62D 1/11 takes precedence) [5]
- 1/10 • • • Hubs; Connecting hubs to steering columns, e.g. adjustable (B62D 1/11 takes precedence) [5]

- 1/11 • • • incorporating energy-absorbing arrangements, e.g. by being yieldable or collapsible (padded linings associated with the steering wheel B60R 21/05; shock absorbers using plastic deformation of members in general F16F 7/12) [5]
- 1/12 • • Hand levers
- 1/14 • • • Tillers, i.e. hand levers operating on steering columns
- 1/16 • • Steering columns
- 1/18 • • • yieldable or adjustable, e.g. tiltable (padded linings associated with the steering column B60R 21/05)

Note(s)

Group B62D 1/181 takes precedence over groups B62D 1/183-B62D 1/187.

- 1/181 • • • • with power actuated adjustment, e.g. with position memory [7]
- 1/183 • • • • adjustable between in-use and out-of-use positions, e.g. to improve access [7]
- 1/184 • • • • Mechanisms for locking columns at selected positions [7]
- 1/185 • • • • adjustable by axial displacement, e.g. telescopically (B62D 1/183, B62D 1/187, B62D 1/19 take precedence) [7]
- 1/187 • • • • with tilt adjustment; with tilt and axial adjustment (B62D 1/183, B62D 1/19 take precedence) [7]
- 1/189 • • • • the entire steering column being tiltable as a unit [7]
- 1/19 • • • • incorporating energy-absorbing arrangements, e.g. by being yieldable or collapsible (shock-absorbers using plastic deformation of members in general F16F 7/12) [5]
- 1/20 • • • Connecting steering column to steering gear
- 1/22 • • Alternative steering-control elements, e.g. for teaching purposes
- 1/24 • not vehicle-mounted
- 1/26 • • mechanical, e.g. by a non-load-bearing guide (railways B61)
- 1/28 • • non-mechanical

3/00 Steering gears (power assisted or power driven B62D 5/00; steering linkages B62D 7/00; for non-deflectable wheels B62D 11/00; gearing in general F16H)

- 3/02 • mechanical
- 3/04 • • of worm type
- 3/06 • • • with screw and nut
- 3/08 • • • • using intermediate balls or the like
- 3/10 • • • with worm engaging in sector or roller gear
- 3/12 • • of rack-and-pinion type
- 3/14 • hydraulic

5/00 Power-assisted or power-driven steering (for non-deflectable wheels B62D 11/00; fluid-pressure servomotors in general F15B)

- 5/02 • mechanical, e.g. using a power-take-off mechanism for taking power from a rotating shaft of the vehicle and applying it to the steering gear
- 5/04 • electrical, e.g. using an electric servo-motor connected to, or forming part of, the steering gear
- 5/06 • fluid, i.e. using a pressurised fluid for most or all the force required for steering a vehicle [4]

- 5/065 • • characterised by specially adapted means for varying pressurised fluid supply based on need, e.g. on-demand, variable assist [7]
- 5/07 • • Supply of pressurised fluid for steering also supplying other consumers [4]
- 5/08 • • characterised by type of valve used (valves in general F16K) [4]
- 5/083 • • • Rotary valves [4]
- 5/087 • • • Sliding spool valves [4]
- 5/09 • • characterised by means for actuating valves [4]
- 5/093 • • • Telemotor driven by steering wheel movement (hydraulic steering gear B62D 3/14) [4]
- 5/097 • • • • gerotor type [4]
- 5/10 • • characterised by type of power unit [4]
- 5/12 • • • Piston and cylinder [4]
- 5/14 • • • Rotary motor [4]
- 5/16 • • • Expansible chamber with flexible wall [4]
- 5/18 • • characterised by power transmitting means [4]
- 5/20 • • specially adapted for particular type of steering gear or particular application (steering gears *per se* B62D 3/00; steering linkages not characterised by being power-assisted or power-driven B62D 7/00) [4]
- 5/22 • • • for rack-and-pinion type [4]
- 5/24 • • • for worm type [4]
- 5/26 • • • for pivoted axles [4]
- 5/28 • • • for pivoted bogies [4]
- 5/30 • • Safety devices, e.g. alternate emergency power supply or transmission means to ensure steering upon failure of the primary steering means [4]
- 5/32 • • • for telemotor systems [4]

6/00 Arrangements for automatically controlling steering depending on driving conditions sensed and responded to, e.g. control circuits (means for initiating a change in direction B62D 1/00; steering valves B62D 5/06; combined with means for inclining the vehicle body or wheels on bends B62D 9/00) [4, 6]

Note(s)

1. When classifying in this group, classification is also made in the appropriate one of groups B62D 1/00 - B62D 5/00 or B62D 7/00 - B62D 19/00 if other aspects of the steering system are of interest.
2. In main group B62D 6/00, but excluding its subgroups, it is desirable to add the indexing codes of groups B62D 101/00 - B62D 137/00.

- 6/02 • responsive only to vehicle speed [4]
- 6/04 • responsive only to forces disturbing the intended course of the vehicle, e.g. forces acting transversely to the direction of vehicle travel [4]
- 6/06 • responsive only to vehicle vibration dampening arrangements (steering dampers for cycles B62K 21/08) [4]
- 6/08 • responsive only to input torque [6]
- 6/10 • • characterised by the means for sensing torque [6]

7/00 Steering linkage; Stub axles or their mountings (B62D 13/00 takes precedence; power-assisted or power-driven steering B62D 5/00) [5]

- 7/02 • for pivoted bogies
- 7/04 • • with more than one wheel
- 7/06 • for individually-pivoted wheels, e.g. on king-pins
- 7/08 • • the pivotal axes being situated in a single plane transverse to the longitudinal centre line of the vehicle

7/09	<ul style="list-style-type: none"> characterised by means varying the ratio between the steering angles of the steered wheels (varying the ratio automatically depending on driving conditions B62D 6/00) [5] 	13/06	<ul style="list-style-type: none"> for backing a normally-drawn trailer
7/10	<ul style="list-style-type: none"> with single-output steering gear 	15/00	Steering not otherwise provided for
7/12	<ul style="list-style-type: none"> with twin-output steering gear 	15/02	<ul style="list-style-type: none"> Steering position indicators [4]
7/14	<ul style="list-style-type: none"> the pivotal axes being situated in more than one plane transverse to the longitudinal centre line of the vehicle, e.g. all-wheel steering 	17/00	Means on vehicle for adjusting camber, castor, or toe-in
7/15	<ul style="list-style-type: none"> characterised by means varying the ratio between the steering angles of the steered wheels (varying the ratio automatically depending on driving conditions B62D 6/00) [5] 	19/00	Radius rods, i.e. distance members
7/16	<ul style="list-style-type: none"> Arrangement of linkage connections (pivots <u>per se</u> F16C) 	Understructures; Superstructures; Vehicle bodies	
7/18	<ul style="list-style-type: none"> Steering knuckles; King-pins 	21/00	Understructures, i.e. chassis frame on which a vehicle body may be mounted (combined frame and vehicle body B62D 23/00)
7/20	<ul style="list-style-type: none"> Links, e.g. track rods (means for adjusting camber, castor, or toe-in B62D 17/00) 	21/02	<ul style="list-style-type: none"> comprising longitudinally or transversely arranged frame members [4]
7/22	<ul style="list-style-type: none"> Arrangements for reducing or eliminating reaction, e.g. vibration, from parts, e.g. wheels, of the steering system [5] 	21/03	<ul style="list-style-type: none"> transverse members providing body support [4]
9/00	Steering deflectable wheels not otherwise provided for (steering-position indicators B62D 15/02)	21/04	<ul style="list-style-type: none"> single longitudinal type
9/02	<ul style="list-style-type: none"> combined with means for inwardly-inclining vehicle body on bends 	21/05	<ul style="list-style-type: none"> pinched frame type, i.e. formed of at least two longitudinal frame sections connected by other longitudinal frame sections of lesser transverse dimension [4]
9/04	<ul style="list-style-type: none"> combined with means for inclining vehicle wheels on bends (B62D 9/02 takes precedence) [5] 	21/06	<ul style="list-style-type: none"> of X-shaped or fork-shaped construction, i.e. having members which form an X or fork as the frame is seen in plan view
11/00	Steering non-deflectable wheels; Steering endless tracks or the like	21/07	<ul style="list-style-type: none"> wide-hipped frame type, i.e. a wide box-shaped mid portion with narrower sections extending from said mid portion in both fore and aft directions [4]
11/02	<ul style="list-style-type: none"> by differentially driving ground-engaging elements on opposite vehicle sides 	21/08	<ul style="list-style-type: none"> built-up with interlaced cross members ("Fachwerkrahmen")
11/04	<ul style="list-style-type: none"> by means of separate power sources 	21/09	<ul style="list-style-type: none"> Means for mounting load bearing surfaces [4]
11/06	<ul style="list-style-type: none"> by means of a single main power source 	21/10	<ul style="list-style-type: none"> in which the main member is plate-like
11/08	<ul style="list-style-type: none"> using brakes or clutches as main steering-effecting means 	21/11	<ul style="list-style-type: none"> with resilient means for suspension [4]
11/10	<ul style="list-style-type: none"> using gearings with differential power outputs on opposite sides, e.g. twin-differential or epicyclic gears 	Note(s)	
11/12	<ul style="list-style-type: none"> using separate change-speed gearings 	This group <u>does not cover</u> subject matter primarily relating to the suspension, with only a nominal recitation of frame structure, which is covered by subclass B60G.	
11/14	<ul style="list-style-type: none"> differential power outputs being effected by additional power supply to one side, e.g. power originating from secondary power source 	21/12	<ul style="list-style-type: none"> assembled from readily-detachable parts
11/16	<ul style="list-style-type: none"> the additional power supply being supplied mechanically 	21/14	<ul style="list-style-type: none"> of adjustable length or width
11/18	<ul style="list-style-type: none"> the additional power supply being supplied hydraulically 	21/15	<ul style="list-style-type: none"> having impact absorbing means, e.g. a frame designed to permanently or temporarily change shape or dimension upon impact with another body (bumpers B60R 19/02; shock absorbers in general F16F) [4]
11/20	<ul style="list-style-type: none"> Endless-track steering having pivoted bogie carrying track (B62D 11/02 takes precedence) 	21/16	<ul style="list-style-type: none"> having fluid storage compartment [4]
11/22	<ul style="list-style-type: none"> Endless-track steering being effected by deflecting endless-track rollers or the like 	21/17	<ul style="list-style-type: none"> forming fluid or electrical conduit means or having other means to accommodate the transmission of a force or signal [4]
11/24	<ul style="list-style-type: none"> Endless-track steering specially adapted for vehicles having both steerable wheels and endless track 	21/18	<ul style="list-style-type: none"> characterised by the vehicle type and not provided for in groups B62D 21/02-B62D 21/17 [4]
12/00	Steering specially adapted for vehicles operating in tandem or having pivotally connected frames (steering endless tracks or the like B62D 11/00; steering specially adapted for trailers B62D 13/00) [4]	21/20	<ul style="list-style-type: none"> trailer type, i.e. a frame specifically constructed for use in a non-powered vehicle [4]
12/02	<ul style="list-style-type: none"> for vehicles operating in tandem [4] 	23/00	Combined superstructure and frame, i.e. monocoque constructions (superstructure sub-units B62D 25/00)
13/00	Steering specially adapted for trailers (combined traction and steering hitches B60D)	24/00	Connections between vehicle body and vehicle frame (B62D 23/00, B62D 33/077 take precedence) [5]
13/02	<ul style="list-style-type: none"> for centrally-pivoted axles 	24/02	<ul style="list-style-type: none"> Vehicle body, not intended to move relatively to the vehicle frame, and mounted on vibration absorbing mountings, e.g. rubber pads [5]
13/04	<ul style="list-style-type: none"> for individually-pivoted wheels 	24/04	<ul style="list-style-type: none"> Vehicle body mounted on resilient suspension for movement relative to the vehicle frame [5]

25/00	Superstructure sub-units; Parts or details thereof not otherwise provided for
25/02	• Side panels
25/04	• Door pillars
25/06	• Fixed roofs (non-fixed roofs or roofs with movable panels B60J 7/00; roof liners B60R 13/02; insulating elements B60R 13/08)
25/07	• • having water drainage or guide means integral with roof structure [4]
25/08	• Front or rear portions
25/10	• • Bonnets or lids
25/12	• • • Parts or details thereof (locks E05B; hinges E05D; counterbalancing means E05F; springs F16F)
25/13	• • • • Water deflectors [5]
25/14	• • Dashboards as superstructure sub-unit (other dashboard aspects B60K)
25/16	• • Mud-guards or wings; Wheel cover panels (equipped with means for freeing wheels or tyres from foreign matter B60S)
25/18	• • • Parts or details thereof, e.g. mud-guard flaps
25/20	• Floors or bottom sub-units
25/22	• Running-boards, steps, or the like, as superstructure sub-unit (other arrangements of steps, ladders, or running-boards in vehicles B60R)
25/24	• Superstructure sub-units with access openings having movable or removable closures (inlet covers for vehicle fuel tanks B60K 15/05) [5]
27/00	Connections between superstructure sub-units
27/02	• rigid
27/04	• resilient
27/06	• readily releasable
29/00	Superstructures characterised by material thereof
29/02	• predominantly of wood
29/04	• predominantly of synthetic material (working of plastics or substances in a plastic state B29)
31/00	Superstructures for passenger vehicles (passenger vehicles specially adapted to co-operate with aircraft or terminal buildings B64F 1/31)
31/02	• for carrying large numbers of passengers, e.g. omnibus
31/04	• with more than one deck
33/00	Superstructures for load-carrying vehicles (in which a load-carrying element is movable B60P; liners B60R 13/00)
33/02	• Platforms; Open load compartments
33/023	• • Sideboard or tailgate structures [5]
33/027	• • • movable [5]
33/03	• • • • by swinging down [5]
33/033	• • • • removable [5]
33/037	• • • • Latching means therefor [5]
33/04	• Enclosed load compartments
33/06	• Drivers' cabs
33/063	• • movable from one position into at least one other position, e.g. tiltable, pivotable about a vertical axis, displaceable from one side of the vehicle to the other [5]
33/067	• • • tiltable [5]
33/07	• • • • characterised by the device for locking the cab in the tilted or in the driving position [5]
33/073	• • • characterised by special adaptations of vehicle control devices [5]

33/077	• characterised by the connection of the superstructure to the vehicle frame [5]
33/08	• • comprising adjustable means (B62D 33/10 takes precedence) [5]
33/10	• • comprising means for the suspension of the superstructure on the frame [5]
35/00	Vehicle bodies characterised by streamlining
35/02	• Streamlining the undersurfaces
37/00	Stabilising vehicle bodies without controlling suspension arrangements
37/02	• by aerodynamic means
37/04	• by means of movable masses
37/06	• • using gyroscopes
39/00	Vehicle bodies not otherwise provided for

41/00 Fittings for identifying vehicles in case of collision; Fittings for marking or recording collision areas
43/00 Spare wheel stowing, holding, or mounting arrangements

43/02	• external to the vehicle body
43/04	• • attached beneath the vehicle body
43/06	• within the vehicle body
43/08	• • and arranged substantially vertical
43/10	• • and arranged substantially horizontal

Motor vehicles or trailers classified according to type; Parts or accessories thereof not otherwise provided for

47/00	Motor vehicles or trailers predominantly for carrying passengers (superstructures B62D 31/00) [3]
47/02	• for large numbers of passengers, e.g. omnibus
49/00	Tractors (of walk type B62D 51/04; endless-track features B62D 55/00)
49/02	• modified to take lifting devices
49/04	• modified to take pushing devices
49/06	• adapted for multi-purpose use
49/08	• having means for preventing overturning or tipping (safety devices for propulsion-unit control, specially adapted for, or arranged in, vehicles B60K 28/00) [4]
51/00	Motor vehicles characterised by the driver not being seated
51/02	• the driver standing in the vehicle
51/04	• the driver walking
51/06	• • Uniaxle walk-type tractors
53/00	Tractor-trailer combinations; Road trains (traction couplings other than fifth-wheel couplings B60D)
53/02	• comprising a uniaxle tractor unit and a uniaxle trailer unit
53/04	• comprising a vehicle carrying an essential part of the other vehicle's load by having supporting means for the front or rear part of the other vehicle
53/06	• • Semi-trailers
53/08	• • Fifth-wheel traction couplings
53/10	• • • with means for preventing accidental uncoupling
53/12	• • • engaging automatically
55/00	Endless-track vehicles (steering aspects B62D 11/00)

55/02	• with tracks and additional ground wheels	57/00	Vehicles characterised by having other propulsion or other ground-engaging means than wheels or endless track, alone or in addition to wheels or endless track (sledges B62B; motor sledges B62M) [5]
55/04	• with tracks and alternative ground wheels, e.g. changeable from endless-track vehicle into wheeled vehicle and <u>vice versa</u>	57/02	• with ground-engaging propulsion means, e.g. walking members
55/06	• with tracks and without ground wheels	57/024	• • specially adapted for moving on inclined or vertical surfaces (endless-track vehicles for ascending or descending stairs B62D 55/075; hand-carts with provision for travelling up or down stairs B62B 5/02) [5]
55/065	• • Multi-track vehicles, i.e. more than two tracks [4]	57/028	• • having wheels and mechanical legs (B62D 57/024 takes precedence; ground-engaging vehicle fittings for supporting, lifting or manoeuvring the vehicle, wholly or in part B60S 9/00) [5]
55/07	• • Mono-track vehicles [4]	57/032	• • with alternately or sequentially lifted supporting base and leg; with alternately or sequentially lifted feet or skid (B62D 57/024 takes precedence) [5]
55/075	• • Tracked vehicles for ascending or descending stairs (magnetic or pneumatic ground-engaging parts B62D 55/265; chairs or personal conveyances specially adapted for patients or disabled persons A61G 5/00) [4]	57/036	• • screw type, e.g. Archimedian screw (B62D 57/024 takes precedence) [5]
55/08	• Endless-track units; Parts thereof	57/04	• having other than ground-engaging propulsion means, e.g. having propellers (arrangement of jet-propulsion units B60K)
55/084	• • Endless-track units or carriages mounted separably, adjustably or extensibly on vehicles, e.g. portable track units (B62D 55/07 takes precedence) [4]	59/00	Trailers with driven ground wheels or the like
55/088	• • with means to exclude or remove foreign matter e.g. sealing means, self-cleaning track links or sprockets, deflector plates or scrapers [4]	59/02	• driven from external propulsion unit
55/092	• • with lubrication means (lubricating in general F16N) [4]	59/04	• driven from propulsion unit on trailer
55/096	• • with noise reducing means [4]	61/00	Motor vehicles or trailers, characterised by the arrangement or number of wheels, not otherwise provided for, e.g. four wheels in diamond pattern
55/10	• • Bogies; Frames (track-tensioning means B62D 55/30)	61/02	• with two road wheels in tandem on the longitudinal centre line of the vehicle
55/104	• • Suspension devices for wheels, rollers, bogies or frames (vehicle suspension in general B60G) [4]	61/04	• • with two other wheels which are coaxial
55/108	• • • with mechanical springs, e.g. torsion bars [4]	61/06	• with only three wheels
55/112	• • • with fluid springs, e.g. hydraulic, pneumatic [4]	61/08	• • with single front wheel
55/116	• • • Attitude or position control of chassis by action on suspension, e.g. to compensate for a slope [4]	61/10	• with more than four wheels
55/12	• • Arrangement, location, or adaptation of driving sprockets	61/12	• with variable number of ground-engaging wheels, e.g. with some wheels arranged higher than others, or with retractable wheels (for manoeuvring purposes only B60S)
55/125	• • • Final drives [4]	63/00	Motor vehicles or trailers not otherwise provided for
55/13	• • • readily interchangeable modular type [4]	63/02	• Motor vehicles
55/135	• • • with dismountable driving crown [4]	63/04	• • Component parts or accessories
55/14	• • Arrangement, location, or adaptation of rollers	63/06	• Trailers (vehicles comprising living accommodation for people, e.g. caravans, camping or like vehicles, B60P 3/32)
55/15	• • Mounting devices, e.g. bushings, axles, bearings, sealings [4]	63/08	• • Component parts or accessories
55/18	• • Tracks (self-cleaning track links B62D 55/088) [4]		
55/20	• • • of articulated type, e.g. chains	65/00	Designing, manufacturing, e.g. assembling, facilitating disassembly, or structurally modifying motor vehicles or trailers, not otherwise provided for
55/205	• • • Connections between track links [4]	65/02	• Joining sub-units or components to, or positioning sub-units or components with respect to, body shell or other sub-units or components [7]
55/21	• • • Links connected by transverse pivot pins [4]	65/04	• • Joining preassembled modular units composed of sub-units performing diverse functions, e.g. engine and bonnet (B62D 65/06-B62D 65/16 take precedence) [7]
55/215	• • • Resilient connections between links [4]	65/06	• • the sub-units or components being doors, windows, openable roofs, lids, bonnets, or weather strips or seals therefor [7]
55/22	• • • Arrangements for preventing or modifying back-flexing	65/08	• • • Weather strips or seals [7]
55/24	• • • of continuously-flexible type, e.g. rubber belts	65/10	• • the sub-units or components being engines, clutches or transmissions [7]
55/247	• • • Gas filled or inflatable flexible tracks (connection of valves to inflatable elastic bodies B60C 29/00) [4]		
55/253	• • • having elements interconnected by one or more cables or like elements [4]		
55/26	• • • Ground-engaging parts or elements		
55/265	• • • having magnetic or pneumatic adhesion [4]		
55/27	• • • having different types of crampons for progression over varying ground [4]		
55/275	• • • with street plate, i.e. means to prevent tread from cutting into road surface [4]		
55/28	• • • detachable		
55/30	• • Track-tensioning means		
55/32	• Assembly, disassembly, repair or servicing of endless-track systems [4]		

B62D

- 65/12 • • the sub-units or components being suspensions, brakes or wheel units [7]
- 65/14 • • the sub-units or components being passenger compartment fittings, e.g. seats, linings, trim, instrument panels [7]
- 65/16 • • the sub-units or components being exterior fittings, e.g. bumpers, lights, wipers [7]
- 65/18 • Transportation, conveyor or haulage systems specially adapted for motor vehicle or trailer assembly lines [7]

67/00 Systematic disassembly of vehicles for recovery of salvageable components, e.g. for recycling (for disposal of vehicles by destroying or transformation B09B 3/00, B09B 5/00) [7]

Indexing scheme associated with group B62D 6/00, but excluding groups B62D 6/02-B62D 6/10, relating to driving conditions sensed and responded to. [5]

- 101/00 Road speed** [5]
- 103/00 Acceleration or deceleration in the direction of travel** [5]
- 105/00 Loss of traction, e.g. wheel spin or skid** [5]
- 107/00 Temperature** [5]
- 109/00 Presence, absence or inactivity of driver or operator, e.g. by sensing the operation of the clutch, brake or throttle** [5]

- 111/00 Forces disturbing the intended course of the vehicle, e.g. forces acting transversely of the direction of travel** [5]
- 113/00 Position of parts of the steering mechanism, e.g. the steered wheels or the steering wheel** [5]
- 115/00 Angle of articulation of articulated vehicle; Angle of tow-bar to towing vehicle** [5]
- 117/00 Angular velocity of steering wheel** [5]
- 119/00 Steering wheel torque** [5]
- 121/00 Force applied to the steering linkage** [5]
- 123/00 Fluid pressure supply for vehicle equipment, e.g. for power-assisted steering; Presence, failure or threshold values thereof; Lubricating or other fluid capacities** [5]
- 125/00 Particular gear ratio selected** [5]
- 127/00 Engine speed** [5]
- 131/00 Load, including height of vehicle dependent on load; State of vehicle vibration damping means** [5]
- 133/00 Trim or inclination, including road gradient** [5]
- 135/00 Air moisture content** [5]
- 137/00 Conditions not specified in groups B62D 101/00-B62D 135/00** [5]