

SECTION H — ELECTRICITY

H03 BASIC ELECTRONIC CIRCUITRY

H03B GENERATION OF OSCILLATIONS, DIRECTLY OR BY FREQUENCY-CHANGING, BY CIRCUITS EMPLOYING ACTIVE ELEMENTS WHICH OPERATE IN A NON-SWITCHING MANNER; GENERATION OF NOISE BY SUCH CIRCUITS (measuring, testing G01R; generators adapted for electrophonic musical instruments G10H; speech synthesis G10L 13/00; masers, lasers H01S; dynamo-electric machines H02K; power inverter circuits H02M; by using pulse techniques H03K; automatic control of generators H03L; starting, synchronisation or stabilisation of generators where the type of generator is irrelevant or unspecified H03L; generation of oscillations in plasma H05H)

Subclass index

GENERATION WITHOUT FREQUENCY-CHANGING

- By means of amplification and feedback; negative resistance.....5/00, 7/00
- By means of transit-time tubes; electron-beam tubes.....9/00, 13/00
- By shock-exciting; Hall effect; radiation source and detectors.....11/00, 15/00, 17/00

GENERATION WITH FREQUENCY- CHANGING

- By multiplication or division of a signal.....19/00
- By combining unmodulated signals.....21/00

PARTICULARITIES OF GENERATED OSCILLATIONS

- Swept-over frequency range; multi-frequency; multiphase; noise.....23/00, 25/00, 27/00, 29/00

OTHER METHODS OF GENERATION.....28/00

DETAILS.....1/00

- | | | | |
|-------------|---|-------------|---|
| 1/00 | Details | 5/26 | • • frequency-determining element being part of bridge circuit in closed ring around which signal is transmitted; frequency-determining element being connected <u>via</u> a bridge circuit to such a closed ring, e.g. Wien-Bridge oscillator, parallel-T oscillator |
| 1/02 | • Structural details of power oscillators, e.g. for heating | | |
| 1/04 | • Reducing undesired oscillations, e.g. harmonics | | |
| 5/00 | Generation of oscillations using amplifier with regenerative feedback from output to input (H03B 9/00, H03B 15/00 take precedence) | 5/28 | • • • active element in amplifier being vacuum tube |
| 5/02 | • Details | 5/30 | • with frequency-determining element being electromechanical resonator |
| 5/04 | • • Modifications of generator to compensate for variations in physical values, e.g. power supply, load, temperature | 5/32 | • • being a piezo-electric resonator (piezo-electric elements in general H01L 41/00) |
| 5/06 | • • Modifications of generator to ensure starting of oscillations | 5/34 | • • • active element in amplifier being vacuum tube (H03B 5/38 takes precedence) |
| 5/08 | • with frequency-determining element comprising lumped inductance and capacitance | 5/36 | • • • active element in amplifier being semiconductor device (H03B 5/38 takes precedence) |
| 5/10 | • • active element in amplifier being vacuum tube (H03B 5/14 takes precedence) | 5/38 | • • • frequency-determining element being connected <u>via</u> bridge circuit to closed ring around which signal is transmitted |
| 5/12 | • • active element in amplifier being semiconductor device (H03B 5/14 takes precedence) | 5/40 | • • being a magnetostrictive resonator (H03B 5/42 takes precedence; magnetostrictive elements in general H01L 41/00) |
| 5/14 | • • frequency-determining element connected <u>via</u> bridge circuit to closed ring around which signal is transmitted | 5/42 | • • frequency-determining element connected <u>via</u> bridge circuit to closed ring around which signal is transmitted |
| 5/16 | • • • active element in amplifier being vacuum tube | | |
| 5/18 | • with frequency-determining element comprising distributed inductance and capacitance | | |
| 5/20 | • with frequency-determining element comprising resistance and either capacitance or inductance, e.g. phase-shift oscillator | 7/00 | Generation of oscillations using active element having a negative resistance between two of its electrodes (H03B 9/00 takes precedence) |
| 5/22 | • • active element in amplifier being vacuum tube (H03B 5/26 takes precedence) | 7/02 | • with frequency-determining element comprising lumped inductance and capacitance |
| 5/24 | • • active element in amplifier being semiconductor device (H03B 5/26 takes precedence) | 7/04 | • • active element being vacuum tube |
| | | 7/06 | • • active element being semiconductor device |
| | | 7/08 | • • • being a tunnel diode |

H03B

- 7/10
 - active element being gas-discharge or arc-discharge tube
- 7/12
 - with frequency-determining element comprising distributed inductance and capacitance
- 7/14
 - active element being semiconductor device
- 9/00 Generation of oscillations using transit-time effects [2]**
- 9/01
 - using discharge tubes [2]
- 9/02
 - using a retarding-field tube (using klystrons H03B 9/04) [2]
- 9/04
 - using a klystron [2]
- 9/06
 - using a reflex klystron [2]
- 9/08
 - using a travelling-wave tube [2]
- 9/10
 - using a magnetron [2]
- 9/12
 - using solid state devices, e.g. Gunn-effect devices [2]
- 9/14
 - and elements comprising distributed inductance and capacitance [3]
- 11/00 Generation of oscillations using a shock-excited tuned circuit (with feedback H03B 5/00)**
- 11/02
 - excited by spark (spark gaps therefor H01T 9/00)
- 11/04
 - excited by interrupter
- 11/06
 - by mechanical interrupter
- 11/08
 - interrupter being discharge tube
- 11/10
 - interrupter being semiconductor device
- 13/00 Generation of oscillations using deflection of electron beam in a cathode-ray tube**
- 15/00 Generation of oscillations using galvano-magnetic devices, e.g. Hall-effect devices, or using super-conductivity effects (galvano-magnetic devices per se H01L 43/00)**
- 17/00 Generation of oscillations using radiation source and detector, e.g. with interposed variable obturator**
- 19/00 Generation of oscillations by non-regenerative frequency multiplication or division of a signal from a separate source (transference of modulation from one carrier to another H03D 7/00)**
- 19/03
 - using non-linear inductance [3]
- 19/05
 - using non-linear capacitance, e.g. varactor diodes [3]
- 19/06
 - by means of discharge device or semiconductor device with more than two electrodes
- 19/08
 - by means of a discharge device
- 19/10
 - using multiplication only
- 19/12
 - using division only
- 19/14
 - by means of a semiconductor device
- 19/16
 - using uncontrolled rectifying devices, e.g. rectifying diodes or Schottky diodes [3]
- 19/18
 - and elements comprising distributed inductance and capacitance [3]
- 19/20
 - being diodes exhibiting charge storage or enhancement effects [3]
- 21/00 Generation of oscillations by combining unmodulated signals of different frequencies (H03B 19/00 takes precedence; frequency changing circuits in general H03D) [3]**
- 21/01
 - by beating unmodulated signals of different frequencies [3]
- 21/02
 - by plural beating, i.e. for frequency synthesis [3]
- 21/04
 - using several similar stages [3]
- 23/00 Generation of oscillations periodically swept over a predetermined frequency range (angle-modulating circuits in general H03C 3/00)**
- 25/00 Simultaneous generation by a free-running oscillator of oscillations having different frequencies**
- 27/00 Generation of oscillations providing a plurality of outputs of the same frequency but differing in phase, other than merely two anti-phase outputs**
- 28/00 Generation of oscillations by methods not covered by groups H03B 5/00-H03B 27/00, including modification of the waveform to produce sinusoidal oscillations (analogue function generators for performing computing operations G06G 7/26; use of transformers for conversion of waveform in ac-ac converters H02M 5/18) [4]**
- 29/00 Generation of noise currents and voltages**