

## SECTION B — PERFORMING OPERATIONS; TRANSPORTING

### B60 VEHICLES IN GENERAL

#### B60D VEHICLE CONNECTIONS (components of brake systems B60T 17/04)

##### Note(s)

Attention is drawn to the Note following the title of class B60.

- |  |  |
|--|--|
| <p><b>1/00</b>    <b>Traction couplings; Hitches; Draw-gear; Towing devices</b> (devices specially adapted for connection between tractors and agricultural machines or implements A01B 59/00; fifth-wheel couplings B62D) [2]</p> <p>1/01    • Traction couplings or hitches characterised by their type [5]</p> <p>1/02    • • Bolt or shackle-type couplings [5]</p> <p>1/04    • • Hook or hook-and-hasps couplings [5]</p> <p>1/06    • • Ball-and-socket hitches [5]</p> <p>1/07    • • Multi-hitch devices, i.e. comprising several hitches of the same or of a different type; Hitch-adaptors, i.e. for converting hitches from one type to another [5]</p> <p>1/14    • Draw-gear or towing devices characterised by their type [4]</p> <p>1/145   • • consisting of an elongated single bar or tube [5]</p> <p>1/155   • • • comprising telescopic or foldable parts [5]</p> <p>1/167   • • consisting of articulated or rigidly assembled bars or tubes forming a V-, Y- or U-shaped draw gear (B60D 1/173 takes precedence) [5]</p> <p>1/173   • • consisting of at least two bars which are not connected or articulated to each other [5]</p> <p>1/18    • • Tow ropes, chains, or the like</p> <p>1/24    • characterised by arrangements for particular functions [5]</p> <p>1/26    • • for remote control, e.g. for releasing [5]</p> <p>1/28    • • for preventing unwanted disengagement, e.g. safety appliances [5]</p> <p>1/30    • • for sway control [5]</p> <p>1/32    • • • involving damping devices [5]</p> <p>1/34    • • • involving springs [5]</p> <p>1/36    • • for facilitating connection, e.g. hitch catchers [5]</p> | <p>1/38    • • • involving auxiliary cables for drawing the trailer to the tractor before coupling [5]</p> <p>1/40    • • • involving a temporarily extensible or alignable member (B60D 1/38 takes precedence) [5]</p> <p>1/42    • • for being adjustable [5]</p> <p>1/44    • • • horizontally [5]</p> <p>1/46    • • • vertically [5]</p> <p>1/48    • characterised by the mounting [5]</p> <p>1/50    • • resiliently mounted (B60D 1/30 takes precedence) [5]</p> <p>1/52    • • removably mounted (B60D 1/56 takes precedence) [5]</p> <p>1/54    • • collapsible or retractable when not in use, e.g. hide-away hitches (B60D 1/52 takes precedence) [5]</p> <p>1/56    • • securing to the vehicle bumper [5]</p> <p>1/58    • Auxiliary devices [5]</p> <p>1/60    • • Covers, caps or guards [5]</p> <p>1/62    • • involving supply lines, electric circuits, or the like [5]</p> <p>1/64    • • • Couplings or joints therefor [5]</p> <p>1/66    • • Props [5]</p> <p><b>3/00</b>    <b>Fittings to facilitate pushing</b> (B60D 1/00 takes precedence; vehicle bumpers B60R 19/02; steering arrangements for backing a normally-drawn trailer B62D 13/06)</p> <p><b>5/00</b>    <b>Gangways for coupled vehicles, e.g. of concertina type</b></p> <p><b>99/00</b>    <b>Subject matter not provided for in other groups of this subclass [2009.01]</b></p> |
|--|--|