

SECTION G — PHYSICS

G05 CONTROLLING; REGULATING

Note(s)

1. This class covers methods, systems, and apparatus for controlling, in general.
2. In this class, the following terms or expressions are used with the meanings indicated:
 - "controlling" means influencing a variable in any way, e.g. changing its direction or its value (including changing it to or from zero), maintaining it constant, limiting its range of variation;
 - "regulation" means maintaining a variable automatically at a desired value or within a desired range of values. The desired value or range may be fixed, or manually varied, or may vary with time according to a predetermined "programme" or according to variation of another variable. Regulation is a form of control;
 - "automatic control" is often used in the art as a synonym for "regulation".
3. Attention is drawn to the Notes following the title of section G, especially as regards the definition of the term "variable".

G05B CONTROL OR REGULATING SYSTEMS IN GENERAL; FUNCTIONAL ELEMENTS OF SUCH SYSTEMS; MONITORING OR TESTING ARRANGEMENTS FOR SUCH SYSTEMS OR ELEMENTS (fluid-pressure actuators or systems acting by means of fluids in general F15B; valves per se F16K; characterised by mechanical features only G05G; sensitive elements, see the appropriate subclasses, e.g. G12B, subclasses of G01, H01; correcting units, see the appropriate subclasses, e.g. H02K)

Note(s)

1. This subclass covers features of control systems or elements for regulating specific variables, which are clearly more generally applicable.
2. This subclass does not cover:
 - a. systems for controlling or regulating non-electric variables in general, which are covered by subclass G05D;
 - b. systems for regulating electric or magnetic variables in general, which are covered by subclass G05F;
 - c. systems specially adapted for the control of particular machines or apparatus provided for in a single other subclass, which are classified in the relevant subclass for such machines or apparatus, provided that there is specific provision for control or regulation relevant to the special adaptation (see Note (5), below). Otherwise, classification is made in the most appropriate place in this subclass.
3. In this subclass, the following terms or expressions are used with the meanings indicated:
 - "automatic controller" means a system, circuit, or device in which a signal from the detecting element is compared with a signal representing the desired value and which operates in such a way as to reduce the deviation. The automatic controller generally does not include the sensitive element, i.e. that element which measures the value of the condition to be corrected, or the correcting element, i.e. that element which adjusts the condition to be corrected;
 - "electric" includes "electromechanical", "electrohydraulic" or "electropneumatic".
4. In this subclass, details of specific control systems are classified in the group relevant to the system, if not otherwise provided for.
5. This Note lists places in the IPC where there is specific provision of the kind referred to in Note (2)(c), above; where such provision is at a general level, the places are listed under the heading "General references"; where the provision is related to programme control, the places are listed under the heading "Places related to group G05B 19/00".

General references

A01K 73/04.....	Spreading or positioning of drawn nets for fishing
A61G 13/02.....	
A61G 15/02.....	Adjustable operating tables, operating chairs, or dental chairs
B01D 3/42.....	Distillation
B01D 24/48.....	
B01D 29/60.....	
B01D 37/04.....	
B01D 46/44.....	Filtration
B01D 53/30.....	Separation of gases or vapours by gas-analysis apparatus
B01D 61/00.....	Separation using semi-permeable membranes
B01J 4/00.....	Feed or outlet in chemical or physical processes
B01J 38/14.....	Oxygen content in oxidation gas for regeneration or reactivation of catalysts
B01J 47/14.....	Ion-exchange processes
B05B 12/02.....	Delivery in spraying systems
B21B 37/00.....	
B21B 39/00.....	Metal-rolling mills
B21K 31/00.....	Positioning tool carriers for forging, pressing or hammering
B22D 11/16.....	Continuous casting of metals
B22D 13/12.....	Centrifugal casting of metals

B22D 17/32.....	Pressure or injection die casting of metals
B22D 18/08.....	Pressure or vacuum casting of metals
B22D 46/00.....	Casting of metals in general
B23B 39/26.....	Tool or work positioning for boring or drilling
B23D 36/00.....	Machines for shearing or similar cutting stock travelling otherwise than in the direction of the cut
B23Q 5/00.....	Driving or feeding mechanisms of machine tools
B23Q 15/00.....	Feed movement, cutting velocity or position of machine tools
B23Q 35/00.....	Copying from a pattern or master model for machine tools
B24B 47/22.....	Position of grinding tool or work
B25J 13/00.....	Manipulators
B26D 5/02.....	Position of cutters in cutting machines
B29C 39/00to.....	
B29C 51/00.....	Shaping techniques for plastic substances
B30B 15/14.....	
B30B 15/16.....	Presses
B41B 27/00.....	Composing machines
B41F 33/00.....	Printing machines or presses
B41J 11/42.....	Feeding sheets or webs in typewriters
B41L 39/00.....	Apparatus or devices for manifolding, duplicating or printing for commercial purposes
B41L 47/56.....	Addressing machines
B60G 17/00to.....	
B60G 21/00.....	Vehicle suspension
B60T 7/00to.....	
B60T 15/00.....	Vehicle brakes
B65B 57/00.....	Machines for packaging
B65G 43/00.....	Conveyors
E02F 3/43.....	Sequence of drive operations for dredging or soil-shifting
E21B 44/00.....	Earth drilling operations
F01K 1/12.....	
F01K 1/16.....	Steam accumulators
F01K 3/00.....	
F01K 7/00.....	
F01K 13/02.....	Steam engine plants
F02C 7/05.....	Air intakes for gas-turbine or jet-propulsion plants
F02C 9/00.....	Gas-turbine plants; Fuel supply in air-breathing jet-propulsion plants
F02D.....	Combustion engines
F02K 1/15.....	
F02K 1/76.....	Jet pipes or nozzles in jet-propulsion plants
F02K 7/00to.....	
F02K 9/00.....	Jet-propulsion plants
F04B 1/00.....	
F04B 27/00.....	
F04B 49/00.....	Positive-displacement machines
F04D 15/00.....	
F04D 27/00.....	Non-positive-displacement pumps, pumping installations, or systems
F16D 43/00.....	
F16D 48/00.....	Clutches
F16F 15/02.....	Suppression of vibrations using fluid means
F16H 59/00to.....	
F16H 63/00.....	Gearings
F22B 35/00.....	Steam boilers
F23G 5/50.....	Incineration of waste
F23N.....	Combustion in combustion apparatus
F24B 1/18.....	Combustion in open fires using solid fuel
F24J 2/40.....	Solar heating
F26B 25/22.....	Drying processes of solid materials or objects
F28B 11/00.....	Steam or vapour condensers
F28D 15/06.....	Heat-exchange apparatus with intermediate heat-transfer medium in closed tubes passing into or through conduit walls, in which the medium condenses and evaporates
F28F 27/00.....	Heat-exchanges or heat-transfer apparatus in general
G06F 11/00.....	Computers
G08G.....	Traffic
G09G.....	Indicating devices using static means to present variable information
G11B 15/00.....	
G11B 19/00.....	Driving, starting or stopping of record carriers
G21C 7/00.....	Nuclear reaction
G21D 3/00.....	Nuclear power plant
H01J 37/30.....	Electron-beam or ion-beam tubes used for localised treatment of objects
H02P.....	Electric motors, generators, or dynamo-electric converters
<u>Places related to group G05B 19/00(programme-control systems)</u>	
A61J 7/04.....	Programmed medicine dispensers

A61L 2/24.....	Disinfection or sterilising
A61N 1/36.....	Heart pace-makers
A63H 17/39.....	Steering-mechanisms for toy vehicles
B04B 13/00.....	Centrifuges
B21B 37/24.....	Thickness of work produced by metal-rolling mills
B21D 7/12.....	Bending metal rods, profiles, or tubes
B23B 39/08.....	
B23B 39/24.....	Boring or drilling machines
B23H 7/20.....	Electrical discharge or electrochemical machining
B23P 21/00.....	Assembling of parts to compose units
B24B 51/00.....	Series of individual steps in grinding a workpiece
B25J 9/00.....	Manipulators
B30B 15/26.....	Presses
B41F 33/16.....	Sequence of operations in printing machines or presses
B41J 11/44.....	Feeding sheets or webs in typewriters
B41L 39/16.....	Sequence of operations in apparatus or devices for manifolding, duplicating or printing for commercial purposes
B41L 47/64.....	Selecting text or image to be printed in addressing machines
B60L 15/20.....	Traction-motor speed of electrically-propelled vehicles
B65H 31/24.....	Piling articles
B66C 13/48.....	
B66C 23/58.....	Crane drives
B67D 7/14.....	Dispensing, delivering or transferring liquids
D05B 19/00.....	
D05B 21/00.....	Sewing machines
D05C 5/04.....	Embroidering machines
D06F 33/00.....	Operations in washing machines
F02D 27/02.....	
F02D 28/00.....	Combustion engines
F02D 41/26.....	Supply of combustible mixture or its constituents to combustion engines
F15B 21/02.....	Fluid-pressure actuator systems
F23N 5/20.....	
F23N 5/22.....	Combustion in combustion apparatus
G01G 19/38.....	Weighing apparatus
G04C 23/08.....	
G04C 23/34.....	Electromechanical clocks or watches
G06C 21/00.....	Mechanically operating digital computers
G06F 9/00.....	Control units for electric digital data processing
G06F 13/10.....	Peripheral devices for electric digital data processing
G06F 15/00.....	Electrically operating digital computers
G06G 7/06.....	Electrically or magnetically operating analogue computers
G09B 7/04.....	
G09B 7/08.....	
G09B 7/12.....	Electrically-operated teaching apparatus or devices
H01H 43/00.....	Electric switches
H01J 37/30.....	Electron-beam or ion-beam tubes used for localised treatment of objects
H03K 17/296.....	Electronic switching or gating
H04Q 3/54.....	Selecting arrangements in electric communication technique

Subclass index**CONTROL SYSTEMS**

Adaptive.....	13/00
Controlled by computer.....	15/00
Involving the use of models or simulators.....	17/00
Controlled by programme.....	19/00
Involving sampling.....	21/00
Open-loop automatic control systems not otherwise provided for.....	24/00

SYSTEM DETAILS

Comparing elements.....	1/00
Anti-hunting arrangements.....	5/00
Internal feedback arrangements.....	6/00
Obtaining smooth engagement or disengagement of automatic control.....	7/00
Safety arrangements.....	9/00
Automatic controllers.....	11/00

TESTING, MONITORING.....23/00**SUBJECT MATTER NOT PROVIDED FOR IN OTHER GROUPS OF THIS SUBCLASS.....99/00**

1/00 Comparing elements, i.e. elements for effecting

comparison directly or indirectly between a desired

- value and existing or anticipated values** (comparing phase or frequency of two electric signals H03D 13/00)
- 1/01 • electric [2]
 - 1/02 • • for comparing analogue signals [2]
 - 1/03 • • for comparing digital signals [2]
 - 1/04 • • with sensing of the position of the pointer of a measuring instrument
 - 1/06 • • • continuous sensing
 - 1/08 • • • stepwise sensing
 - 1/11 • fluidic [2]
- 5/00 Anti-hunting arrangements**
- 5/01 • electric
 - 5/04 • fluidic [2]
- 6/00 Internal feedback arrangements for obtaining particular characteristics, e.g. proportional, integral, differential** (in automatic controllers G05B 11/00)
- 6/02 • electric
 - 6/05 • fluidic [2]
- 7/00 Arrangements for obtaining smooth engagement or disengagement of automatic control**
- 7/02 • electric [2]
 - 7/04 • fluidic [2]
- 9/00 Safety arrangements** (G05B 7/00 takes precedence; safety arrangements in programme-control systems G05B 19/048, G05B 19/406; safety valves F16K 17/00; emergency protective circuit arrangements in general H02H)
- 9/02 • electric
 - 9/03 • • with multiple-channel loop, i.e. redundant control systems [2]
 - 9/05 • fluidic [2]
- 11/00 Automatic controllers** (G05B 13/00 takes precedence)
- 11/01 • electric
 - 11/06 • • in which the output signal represents a continuous function of the deviation from the desired value, i.e. continuous controllers (G05B 11/26 takes precedence)
 - 11/10 • • • the signal transmitted being dc
 - 11/12 • • • the signal transmitted being modulated on an ac carrier
 - 11/14 • • in which the output signal represents a discontinuous function of the deviation from the desired value, i.e. discontinuous controllers (G05B 11/26 takes precedence)
 - 11/16 • • • Two-step controllers, e.g. with on/off action
 - 11/18 • • • Multi-step controllers
 - 11/26 • • in which the output signal is a pulse-train
 - 11/28 • • • using pulse-height modulation; using pulse-width modulation
 - 11/30 • • • using pulse-frequency modulation
 - 11/32 • • with inputs from more than one sensing element; with outputs to more than one correcting element
 - 11/36 • • with provision for obtaining particular characteristics, e.g. proportional, integral, differential
 - 11/38 • • • for obtaining a proportional characteristic
 - 11/40 • • • for obtaining an integral characteristic
 - 11/42 • • • for obtaining a characteristic which is both proportional and time-dependent, e.g. P. I., P. I. D.
 - 11/44 • pneumatic only
 - 11/46 • • without auxiliary power
- 11/48 • • with auxiliary power
 - 11/50 • • • in which the output signal represents a continuous function of the deviation from the desired value, i.e. continuous controllers
 - 11/52 • • • in which the output signal represents a discontinuous function of the deviation from the desired value, i.e. discontinuous controllers
 - 11/54 • • • • Two-step controllers, e.g. with on/off action
 - 11/56 • • • • Multi-step controllers
 - 11/58 • • with inputs from more than one sensing element; with outputs to more than one correcting element
 - 11/60 • hydraulic only
- 13/00 Adaptive control systems, i.e. systems automatically adjusting themselves to have a performance which is optimum according to some preassigned criterion** (G05B 19/00 takes precedence; details of the computer G06F 15/18) [3]
- 13/02 • electric
 - 13/04 • • involving the use of models or simulators [3]
- 15/00 Systems controlled by a computer** (G05B 13/00, G05B 19/00 take precedence; automatic controllers with particular characteristics G05B 11/00; computers *per se* G06) [3]
- 15/02 • electric
- 17/00 Systems involving the use of models or simulators of said systems** (G05B 13/00, G05B 15/00, G05B 19/00 take precedence; analogue computers for specific processes, systems or devices, e.g. simulators, G06G 7/48) [3]
- 17/02 • electric
- 19/00 Programme-control systems** (specific applications, see the relevant places, e.g. A47L 15/46; clocks with attached or built-in means operating any device at a preselected time interval G04C 23/00; marking or sensing record carriers with digital information G06K; information storage G11; time or time-programme switches which automatically terminate their operation after the programme is completed H01H 43/00)
- 19/02 • electric
 - 19/04 • • Programme control other than numerical control, i.e. in sequence controllers or logic controllers (G05B 19/418 takes precedence; numerical control G05B 19/18)
 - 19/042 • • • using digital processors (G05B 19/05 takes precedence) [6]
 - 19/045 • • • using logic state machines, consisting only of a memory or a programmable logic device containing the logic for the controlled machine and in which the state of its outputs is dependent on the state of its inputs or part of its own output states, e.g. binary decision controllers, finite state controllers [6]
 - 19/048 • • • Monitoring; Safety [6]
 - 19/05 • • • Programmable logic controllers, e.g. simulating logic interconnections of signals according to ladder diagrams or function charts [5]
 - 19/06 • • • using cams, discs, rods, drums, or the like (mechanical programme-control apparatus G05G 21/00)
 - 19/07 • • • where the programme is defined in the fixed connection of electrical elements, e.g. potentiometers, counters, transistors [6]
 - 19/08 • • • using plugboards, cross-bar distributors, matrix switches, or the like
 - 19/10 • • • using selector switches

- 19/12 • • • using record carriers
 - 19/14 • • • • using punched cards or tapes
 - 19/16 • • • • using magnetic record carriers
 - 19/18 • • Numerical control (NC), i.e. automatically operating machines, in particular machine tools, e.g. in a manufacturing environment, so as to execute positioning, movement or co-ordinated operations by means of programme data in numerical form (G05B 19/418 takes precedence) **[6]**
 - 19/19 • • • characterised by positioning or contouring control systems, e.g. to control position from one programmed point to another or to control movement along a programmed continuous path **[3, 6]**
- Note(s)**
- In this group, the measuring system for an axis is used to measure the displacement along that axis. This measurement is used as position-feedback in the servo-control system.
- 19/21 • • • • using an incremental digital measuring device **[3]**
 - 19/23 • • • • • for point-to-point control **[3]**
 - 19/25 • • • • • for continuous-path control **[3]**
 - 19/27 • • • • using an absolute digital measuring device **[3]**
 - 19/29 • • • • • for point-to-point control **[3]**
 - 19/31 • • • • • for continuous-path control **[3]**
 - 19/33 • • • • using an analogue measuring device **[3]**
 - 19/35 • • • • • for point-to-point control **[3]**
 - 19/37 • • • • • for continuous-path control **[3]**
 - 19/39 • • • • using a combination of the means covered by at least two of the preceding groups G05B 19/21, G05B 19/27 and G05B 19/33 **[3]**
 - 19/40 • • • • Open loop systems, e.g. using stepping motor **[3]**
 - 19/401 • • • characterised by control arrangements for measuring, e.g. calibration and initialisation, measuring workpiece for machining purposes (G05B 19/19 takes precedence) **[6]**
 - 19/402 • • • characterised by control arrangements for positioning, e.g. centring a tool relative to a hole in the workpiece, additional detection means to correct position (G05B 19/19 takes precedence) **[6]**
 - 19/404 • • • characterised by control arrangements for compensation, e.g. for backlash, overshoot, tool offset, tool wear, temperature, machine construction errors, load, inertia (G05B 19/19, G05B 19/41 take precedence) **[6]**
 - 19/406 • • • characterised by monitoring or safety (G05B 19/19 takes precedence) **[6]**
 - 19/4061 • • • • Avoiding collision or forbidden zones **[6]**
 - 19/4062 • • • • Monitoring servoloop, e.g. overload of servomotor, loss of feedback or reference **[6]**
 - 19/4063 • • • • Monitoring general control system (G05B 19/4062 takes precedence) **[6]**
 - 19/4065 • • • • Monitoring tool breakage, life or condition **[6]**
 - 19/4067 • • • • Restoring data or position after power failure or other interruption **[6]**
 - 19/4068 • • • • Verifying part programme on screen, by drawing or other means **[6]**
 - 19/4069 • • • • Simulating machining process on screen (G05B 19/4068 takes precedence) **[6]**
 - 19/408 • • • • characterised by data handling or data format, e.g. reading, buffering or conversion of data **[6]**
 - 19/409 • • • • characterised by using manual data input (MDI) or by using control panel, e.g. controlling functions with the panel; characterised by control panel details, by setting parameters (G05B 19/408, G05B 19/4093 take precedence) **[6]**
 - 19/4093 • • • • characterised by part programming, e.g. entry of geometrical information as taken from a technical drawing, combining this with machining and material information to obtain control information, named part programme, for the NC machine **[6]**
 - 19/4097 • • • • characterised by using design data to control NC machines, e.g. CAD/CAM (G05B 19/4093 takes precedence; CAD in general G06F 17/50) **[6]**
 - 19/4099 • • • • Surface or curve machining, making 3D objects, e.g. desktop manufacturing **[6]**
 - 19/41 • • • • characterised by interpolation, e.g. the computation of intermediate points between programmed end points to define the path to be followed and the rate of travel along that path (G05B 19/25, G05B 19/31, G05B 19/37, G05B 19/39, G05B 19/40 take precedence) **[3, 6]**
 - 19/4103 • • • • Digital interpolation **[6]**
 - 19/4105 • • • • Analog interpolation **[6]**
 - 19/414 • • • • Structure of the control system, e.g. common controller or multiprocessor systems, interface to servo, programmable interface controller **[6]**
 - 19/4155 • • • • characterised by programme execution, i.e. part programme or machine function execution, e.g. selection of a programme **[6]**
 - 19/416 • • • characterised by control of velocity, acceleration or deceleration (G05B 19/19 takes precedence) **[6]**
 - 19/418 • • • Total factory control, i.e. centrally controlling a plurality of machines, e.g. direct or distributed numerical control (DNC), flexible manufacturing systems (FMS), integrated manufacturing systems (IMS), computer integrated manufacturing (CIM) **[6]**
 - 19/42 • • • Recording and playback systems, i.e. in which the programme is recorded from a cycle of operations, e.g. the cycle of operations being manually controlled, after which this record is played back on the same machine
 - 19/421 • • • • Teaching successive positions by mechanical means, e.g. by mechanically-coupled handwheels to position tool head or end effector (G05B 19/423 takes precedence) **[6]**
 - 19/423 • • • • Teaching successive positions by walk-through, i.e. the tool head or end effector being grasped and guided directly, with or without servo-assistance, to follow a path **[6]**
 - 19/425 • • • • Teaching successive positions by numerical control, i.e. commands being entered to control the positioning servo of the tool head or end effector **[6]**
 - 19/427 • • • • Teaching successive positions by tracking the position of a joystick or handle to control the positioning servo of the tool head, master-slave control (G05B 19/423 takes precedence) **[6]**
 - 19/43 • • fluidic **[3]**
 - 19/44 • • • pneumatic **[3]**
 - 19/46 • • • hydraulic **[3]**

G05B

- 21/00 **Systems involving sampling of the variable controlled** (G05B 13/00-G05B 19/00 take precedence; transmission systems for measured values G08C; electronic switching or gating H03K 17/00)
- 21/02 • electric
- 23/00 **Testing or monitoring of control systems or parts thereof** (monitoring of programme-control systems G05B 19/048, G05B 19/406)
- 23/02 • Electric testing or monitoring
- 24/00 **Open-loop automatic control systems not otherwise provided for [2]**
- 24/02 • electric [2]
- 24/04 • fluidic [2]
- 99/00 **Subject matter not provided for in other groups of this subclass [2006.01]**

G05D SYSTEMS FOR CONTROLLING OR REGULATING NON-ELECTRIC VARIABLES (for continuous casting of metals B22D 11/16; valves per se F16K; sensing non-electric variables, see the relevant subclasses of G01; for regulating electric or magnetic variables G05F)

Note(s)

1. This subclass does not cover features of general applicability to regulating systems, e.g. anti-hunting arrangements, which are covered by subclass G05B.
2. In this subclass, the following term is used with the meaning indicated:
 - "systems" includes self-contained devices such as speed governors, pressure regulators.
3. Control systems specially adapted for particular apparatus, machines or processes are classified in the subclasses for the apparatus, machines or processes, provided that there is specific provision for control or regulation relevant to the special adaptation, either at a detailed level (e.g. A21B 1/40: "for regulating temperature in bakers' ovens") or at a general level (e.g. B23K 9/095: "for automatic control of welding parameters in arc welding"). Otherwise, classification is made in the most appropriate place in this subclass. The following are lists of places where there is specific provision of the kind referred to above. Where such provision is at a detailed level, the places have been grouped according to the main groups of this subclass. Where the provision is at a general level (e.g. of a kind appropriate to more than one of the main groups specified in the lists, or to main groups G05D 27/00 or G05D 29/00), the places are listed under the title "General References".

Places related to

A01B 69/00.....Agricultural machines or implements
A63H 17/36.....Toy vehicles
B60V 1/11.....Air-cushion vehicles
B60W 30/10.....Road vehicle path control
B62D 1/00.....Steering controls of motor vehicles or trailers, i.e. means for initiating a change of direction
B62D 6/00.....Arrangements for automatically controlling the steering depending on driving conditions
B62D 55/116.....Chassis of endless-tracked vehicles
B63H 25/00.....Marine steering; control of waterborne vessels
B64C 13/00-B64C 15/00.....Controlling aircraft
B64D 25/11.....Controlling attitude or direction of aircraft ejector seats
B64G 1/24.....Cosmonautic vehicles
F41G 7/00.....Self-propelled missiles
F42B 15/01.....Guided missiles
F42B 19/01.....Marine torpedoes

Places related to

A43D 119/00.....Footwear manufacture
B21K 31/00.....Tool carriers in forging or pressing
B23B 39/26.....Pattern-controlled boring or drilling tools
B23D 1/30, B23D 3/06, B23D 5/04 Planing or slotting machines controlled by copying device
B23H 7/18.....Electrode to workpiece spacing in electric discharge and electrochemical machining
B23K 26/02.....Workpiece in laser welding or cutting
B23K 37/04.....Workpiece in welding
B23K 37/06.....Molten metal in welding
B23Q 5/20.....Spindles in machine tools
B23Q 15/00, B23Q 16/00.....Tool or work position in machine tools
B23Q 35/00.....Tools controlled by pattern or master model
B24B 17/00.....Grinding controlled by patterns, drawings, magnetic tape or the like
B24B 47/22.....Starting position in grinding
B30B 15/24.....Actuating members in presses
B62D 55/116.....Chassis of tracked vehicles
B65H 23/18.....Web-advancing mechanisms
E02F 3/43.....Dippers or buckets in dredgers
F15B 9/00.....Fluid-pressure servomotors with follow-up action
F24J 2/38.....Tracking of solar heat collectors
G03F 9/00.....Photomechanical production of patterned or textured surfaces
G11B 5/588.....Rotating heads in information storage systems
G21C 7/12.....Movement of control elements in nuclear reactors

Places related to

A24B 7/14.....Tobacco cutting

B05C 11/02.....	Thickness of coating of fluent material on surface
B21B 37/16.....	Thickness, width, diameter or other transverse dimensions of the products of metal-rolling mills
C03B 18/04.....	Dimension of glass ribbon
D21F 7/06.....	Thickness of layer in paper making

Places related to

A45D 20/26.....	Air in hair drying helmets
A61M 5/168.....	Flow of media to the human body
B03C 3/36.....	Gases or vapour in electrostatic separators
B05C 11/10.....	Fluent material in coating devices
B67D 1/12.....	Dispensing beverages on draught
B67D 7/28.....	Transferring liquids
C10K 1/28.....	Gas purifiers
E21B 21/08.....	Flushing boreholes
E21B 43/12.....	Obtaining liquids from wells
F01D 17/00.....	Flow in non-positive-displacement machines or systems
F01M 1/16.....	Lubrication arrangements
F01P 7/00.....	Coolant flow in cooling devices
F02C 9/16, F02C 9/50.....	Gas-turbine working fluid
F16L 55/027.....	Throttle passages in pipes
F24F 11/00.....	Air-flow or supply of heating or cooling fluids in air treatment arrangements
F26B 21/12.....	Air or gas flow in dryers
G01G 11/08.....	Continuous flow weighing apparatus
G21D 3/14.....	Coolant in nuclear power plant

Places related to

B01D 21/34.....	Liquid level in sedimentation arrangements
B41L 27/04.....	Ink level in printing, manifolding or duplicating arrangements
F22D 5/00.....	Feed water for boilers
H01J 1/10, H01J 13/14.....	Liquid pool electrodes in electric discharge tubes or lamps

Places related to

B01D 21/32.....	Density in sedimentation arrangements
B01F 15/04.....	Mixers
B24C 7/00.....	Abrasive blasts
B28C 7/00.....	Mixtures of clays or cements
B65G 53/66.....	Bulk material conveyors
F02K 3/075.....	Flow ratio in jet-propulsion plants

Places related to

B21C 1/12.....	Drum speed in metal drawing
B23Q 15/00.....	Cutting velocity of tool or work
B30B 15/20.....	Ram speed in presses
B60K 31/00.....	Setting or limiting speed of vehicles
B60L 15/00.....	Electrically-propelled vehicles
B60W 30/14.....	Road vehicle cruise control
B64D 31/08.....	Cruising speed of aircraft
D01D 1/09.....	Feed rate in manufacture of artificial filaments, threads, fibres, bristles or ribbons
D01G 15/36.....	Carding machines
D02H 13/14.....	Warping, beaming or leasing machines
D03D 51/16.....	Cyclically varying speed of looms
G01N 30/32.....	Speed of fluid carrier in chemical analysis
G11B 15/46.....	Filamentary or web record carriers or heads for such carriers in information storage systems
G11B 19/28.....	Non-filamentary, non-web record carriers, or heads for such carriers in information storage systems

Places related to

B25D 9/26.....	Portable percussive tools
B30B 15/22.....	Ram pressure in presses
B65H 59/00.....	Tension in filamentary material
B65H 77/00.....	Tension in webs, tapes, filamentary material
B66D 1/50.....	Rope, cable or chain tension
D03D 49/04.....	Tension in looms
D05B 47/04.....	Tension in sewing machines
D21F 3/06.....	Pressure in paper-making machines
F26B 13/12.....	Drying fabrics
F26B 21/10.....	Pressure in dryers
G11B 15/43.....	Record carrier tension in information storage arrangements

Places related to

B60C 23/00.....	Tyre pressure
B63C 11/08.....	Air within diving suit
B64D 13/00.....	Aircraft air-pressure
B65G 53/66.....	Bulk material conveyors
D01D 1/09.....	Manufacture of artificial filaments, threads, fibres, bristles or ribbons
E21B 21/08.....	Flushing boreholes
F01M 1/16.....	Lubrication arrangements
G01N 30/32.....	Pressure of fluid carrier in chemical analysis

H01J 7/14.....Pressure in electric discharge tubes or lamps

H01K 1/52.....Pressure in electric incandescent lamps

Places related to

B25D 9/26.....Portable percussion tools

B65G 27/32.....Jigging conveyors

Places related to

B01D 21/32.....Density in sedimentation arrangements

B01D 53/30.....Treating gases or vapours

G01N 30/34.....Composition of fluid carrier in chemical analysis

Places related to

A01G 25/16.....Watering gardens, fields, sports grounds or the like

A01K 41/04.....Poultry incubators

A24B 9/00.....Tobacco products

F24F 11/00.....Air conditioning

F26B 21/08.....Dryers

Places related to

A21B 1/40.....Bakers' ovens

A45D 6/20.....Hair curlers

B21C 31/00.....Metal extruding

B60C 23/00.....Tyre temperature

B64G 1/50.....Cosmonautic vehicles

C03B 18/18, C03B 18/22.....Float baths in glass making

D01D 1/09.....Manufacture of artificial filaments, threads, fibres, bristles or ribbons

D04B 35/30.....Knitting machines

D06F 75/26.....Hand irons

D21F 5/06.....Paper-making machines

F01M 5/00.....Lubricant in lubrication arrangements

F16N 7/08.....Arrangements for supplying oil or unspecified lubricant from a reservoir

F22G 5/00.....Steam superheat

F26B 21/10.....Dryers

G01N 30/30.....Temperature of fluid carrier in chemical analysis

H01M 10/60.....Electric storage cells

H05B 6/06, H05B 6/50, H05B 6/68 Dielectric, induction or microwave heating

H05G 1/36.....Anode of X-ray tube

Places related to

B41B 21/08.....Photographic composing machines

H01S 3/10, H05B 33/08, H05B 35/00-H05B 43/00 Lasers and other light sources

General references

A01D 41/127.....Combines

A01J 5/007.....Milking machines

B23K 9/095.....Welding parameters

B23Q 35/00.....Copying

B24B 17/00, B24B 49/00.....Grinding or polishing

B24C 7/00.....Abrasive blasts

B67D 1/12.....Dispensing beverages on draught

F23C 10/28.....Combustion apparatus in which combustion takes place in a fluidised bed of fuel or other particles

G03G 21/20.....Electrographic, electrophotographic or magnetographic processes

H02P 5/00-H02P 9/00.....Dynamo-electric motors or generators

Subclass index

CONTROL OF: SPEED OR ACCELERATION; FORCE; PRESSURE; POWER; MECHANICAL

OSCILLATIONS.....13/00, 15/00, 16/00, 17/00, 19/00

CONTROL OF: FLOW; LEVEL; RATIO.....7/00, 9/00, 11/00

CONTROL OF: TEMPERATURE; HUMIDITY; VISCOSITY; CHEMICAL OR PHYSICO-CHEMICAL

VARIABLES; LIGHT INTENSITY.....23/00, 22/00, 24/00, 21/00, 25/00

CONTROL OF: POSITION, DIRECTION, DIMENSIONS.....1/00-5/00

SIMULTANEOUS CONTROL OF TWO OR MORE VARIABLES.....27/00, 29/00

SUBJECT MATTER NOT PROVIDED FOR IN OTHER GROUPS OF THIS SUBCLASS.....99/00

1/00 Control of position, course, altitude, or attitude of land, water, air, or space vehicles, e.g. automatic pilot
(radio navigation systems or analogous systems using other waves G01S)

1/02 • Control of position or course in two dimensions [2]

1/03 • • using near-field transmission systems, e.g. inductive-loop type

1/04 • Control of altitude or depth

1/06 • • Rate of change of altitude or depth

1/08 • Control of attitude, i.e. control of roll, pitch, or yaw

1/10 • Simultaneous control of position or course in three dimensions (G05D 1/12 takes precedence)

1/12 • Target-seeking control

3/00 Control of position or direction (G05D 1/00 takes precedence; for numerical control G05B 19/18)

3/10 • without using feedback [3]

3/12 • using feedback [3]

3/14	• • using an analogue comparing device [3]	13/24	• • • counterbalanced by two or more different appliances acting simultaneously upon the riser, e.g. with both spring force and fluid pressure, with both spring force and electromagnetic force
3/16	• • • whose output amplitude can only take a number of discrete values (G05D 3/18 takes precedence) [3]	13/26	• • • with provision for modulating the degree of non-uniformity of speed
3/18	• • • delivering a series of pulses [3]	13/28	• • • with provision for performing braking effects in case of increased speed
3/20	• • using a digital comparing device [3]	13/30	• • Governors characterised by fluid features in which the speed of a shaft is converted into fluid pressure (transducers converting variations of physical quantities into fluid-pressure variations F15B 5/00)
5/00	Control of dimensions of material	13/32	• • • using a pump
5/02	• of thickness, e.g. of rolled material	13/34	• with auxiliary non-electric power (fluid-pressure converters F15B 3/00) [2]
5/03	• • characterised by the use of electric means	13/36	• • using regulating devices with proportional band, i.e. P. regulating devices
5/04	• of the size of items, e.g. of particles	13/38	• • • involving centrifugal governors of fly-weight type
5/06	• • characterised by the use of electric means	13/40	• • • involving centrifugal governors of pump type
7/00	Control of flow (level control G05D 9/00; ratio control G05D 11/00; weighing apparatus G01G)	13/42	• • • involving fluid governors of flow-controller type, i.e. the width of liquid flow being controlled by fly-weights
7/01	• without auxiliary power	13/44	• • • involving fluid governors of jet type
7/03	• with auxiliary non-electric power [2]	13/46	• • using regulating devices with proportional band and integral action, i.e. P.I. regulating devices
7/06	• characterised by the use of electric means	13/48	• • • involving resilient restoring mechanisms
9/00	Level control, e.g. controlling quantity of material stored in vessel	13/50	• • • involving connecting means for superimposing a proportional regulating device and an integral regulating device
9/02	• without auxiliary power	13/52	• • using regulating devices with proportional band and derivative action, i.e. P.D. regulating devices
9/04	• with auxiliary non-electric power [2]	13/54	• • • involving centrifugal governors of fly-weight type exerting an acceleratory effect
9/12	• characterised by the use of electric means	13/56	• • • involving restoring mechanisms exerting a delay effect
11/00	Ratio control (control of chemical or physico-chemical variables, e.g. pH-value, G05D 21/00; humidity control G05D 22/00; control of viscosity G05D 24/00) [3]	13/58	• • • involving means for connecting a speed-regulating device and an acceleration-regulating device
11/02	• Controlling ratio of two or more flows of fluid or fluent material	13/60	• • using regulating devices with proportional band, derivative, and integral action, i.e. P.I.D. regulating devices
11/03	• • without auxiliary power	13/62	• characterised by the use of electric means, e.g. use of a tachometric dynamo, use of a transducer converting an electric value into a displacement
11/035	• • with auxiliary non-electric power [2]	13/64	• Compensating the speed difference between engines meshing by a differential gearing or the speed difference between a controlling shaft and a controlled shaft
11/04	• • • by sensing weight of individual components, e.g. gravimetric procedure	13/66	• Governor units providing for co-operation with control dependent upon a variable other than speed
11/06	• • • by sensing density of mixture, e.g. using aerometer	15/00	Control of mechanical force or stress; Control of mechanical pressure
11/08	• • • by sensing concentration of mixture, e.g. by measuring pH-value [3]	15/01	• characterised by the use of electric means
11/10	• • • • by sensing moisture of non-aqueous liquids	16/00	Control of fluid pressure
11/12	• • • by sensing viscosity of mixture	16/02	• Modifications to reduce the effects of instability, e.g. due to vibrations, friction, abnormal temperature, overloading, unbalance (vibration-dampers F16F 7/00)
11/13	• • characterised by the use of electric means	16/04	• without auxiliary power
11/16	• Controlling mixing ratio of fluids having different temperatures, e.g. by sensing the temperature of a mixture of fluids having different viscosities	16/06	• • the sensing element being a flexible member yielding to pressure, e.g. diaphragm, bellows, capsule
13/00	Control of linear speed; Control of angular speed; Control of acceleration or deceleration, e.g. of a prime mover (synchronising telegraph receiver and transmitter H04L 7/00)	16/08	• • • Control of liquid pressure
13/02	• Details		
13/04	• • providing for emergency tripping of an engine in case of exceeding maximum speed		
13/06	• • providing for damping of erratic vibrations in governors		
13/08	• without auxiliary power		
13/10	• • Centrifugal governors with fly-weights		
13/12	• • • Details		
13/14	• • • • Fly-weights; Mountings thereof; Adjusting equipment for limits, e.g. temporarily		
13/16	• • • • Risers; Transmission gear therefor; Restoring mechanisms therefor		
13/18	• • • counterbalanced by spider springs acting immediately upon the fly-weights		
13/20	• • • counterbalanced by spider springs acting upon the articulated riser		
13/22	• • • counterbalanced by fluid pressure acting upon the articulated riser		

G05D

- 16/10 • • the sensing element being a piston or plunger
- 16/12 • • the sensing element being a float
- 16/14 • with auxiliary non-electric power [2]
- 16/16 • • derived from the controlled fluid
- 16/18 • • derived from an external source
- 16/20 • characterised by the use of electric means

- 17/00 Control of torque; Control of mechanical power**
- 17/02 • characterised by the use of electric means

- 19/00 Control of mechanical oscillations, e.g. of amplitude, of frequency, of phase**
- 19/02 • characterised by the use of electric means

- 21/00 Control of chemical or physico-chemical variables, e.g. pH-value [3]**
- 21/02 • characterised by the use of electric means

- 22/00 Control of humidity [2]**
- 22/02 • characterised by the use of electric means

- 23/00 Control of temperature** (automatic switching arrangements for electric heating apparatus H05B 1/02)
- 23/01 • without auxiliary power
- 23/02 • • with sensing element expanding and contracting in response to changes of temperature (G05D 23/13 takes precedence)
- 23/08 • • • with bimetallic element (arrangement of valves and flow lines specially adapted for mixing fluid F16K 11/00)
- 23/10 • • • with snap-action elements (for valves F16K 31/56)
- 23/12 • • with sensing element responsive to pressure or volume changes in a confined fluid
- 23/13 • • by varying the mixing ratio of two fluids having different temperatures
- 23/185 • with auxiliary non-electric power [2]
- 23/19 • characterised by the use of electric means
- 23/20 • • with sensing elements having variation of electric or magnetic properties with change of temperature (G05D 23/13 takes precedence)

- 23/22 • • • the sensing element being a thermocouple
- 23/24 • • • the sensing element having a resistance varying with temperature, e.g. thermistor
- 23/26 • • • the sensing element having a permeability varying with temperature
- 23/27 • • with sensing element responsive to radiation
- 23/275 • • with sensing element expanding, contracting, or fusing in response to changes of temperature
- 23/30 • • Automatic controllers with an auxiliary heating device affecting the sensing element, e.g. for anticipating change of temperature (automatic controllers in general and not restricted to control of temperature G05B)
- 23/32 • • • with provision for adjustment of the effect of the auxiliary heating device, e.g. as a function of time

- 24/00 Control of viscosity**
- 24/02 • characterised by the use of electric means

- 25/00 Control of light, e.g. intensity, colour, phase** (mechanically operable parts of lighting devices for the control of light F21V; optical devices or arrangements using movable or deformable elements for controlling light independent of the light source G02B 26/00; devices or arrangements, the optical operation of which is modified by changing the optical properties of the medium of the devices or arrangements for the control of light, circuit arrangements specially adapted therefor, control of light by electro-magnetic waves, electrons or other elementary particles G02F 1/00) [4]
- 25/02 • characterised by the use of electric means

- 27/00 Simultaneous control of variables covered by two or more of main groups G05D 1/00-G05D 25/00**
- 27/02 • characterised by the use of electric means

- 29/00 Simultaneous control of electric and non-electric variables**

- 99/00 Subject matter not provided for in other groups of this subclass [2006.01]**

G05F SYSTEMS FOR REGULATING ELECTRIC OR MAGNETIC VARIABLES (regulating the timing or recurrence frequency of pulses in radar or radio navigation systems G01S; regulation of current or voltage, specially adapted for use in electronic time-pieces G04G 19/02; closed-loop systems for regulating non-electric variables by electric means G05D; regulating power supply of digital computers G06F 1/26; for obtaining desired operating characteristics of electromagnets with armatures H01F 7/18; regulating electric power distribution networks H02J; regulating the charging of batteries H02J 7/00; regulating of the output of static converters, e.g. switching regulators, H02M; regulation of the output of electric generators H02N, H02P 9/00; controlling transformers, reactors or choke coils H02P 13/00; regulating frequency response, gain, maximum output, amplitude or bandwidth of amplifiers H03G; regulating tuning of resonant circuits H03J; controlling generators of electronic oscillations or pulses H03L; regulating characteristics of transmission lines H04B; controlling electric light sources H05B 37/02, H05B 39/04, H05B 41/36; electric control of X-ray apparatus H05G 1/30) [4, 5]

Note(s)

1. This subclass covers:
 - systems only;
 - use of hydraulic, pneumatic, mechanical, and electrical motors for varying electric characteristics of devices which restore the quantity regulated;
 - the combination of static converters and current or voltage regulators, if the essential characteristic resides in the combination.
2. This subclass does not cover elements per se, which are covered by the relevant subclasses.

1/00 Automatic systems in which deviations of an electric quantity from one or more predetermined values are detected at the output of the system and fed back to a device within the system to restore the detected

quantity to its predetermined value or values, i.e. retroactive systems

- 1/02 • Regulating electric characteristics of arcs (arrangements for feeding or moving of electrodes for spot or seam welding or cutting B23K 9/12; arrangements for feeding electrodes for electric heating or electric lighting H05B 7/109, H05B 31/18; automatic control of power for heating by discharge H05B 7/148) [2]
- 1/04 • • by means of saturable magnetic devices
- 1/06 • • by means of discharge tubes
- 1/08 • • by means of semiconductor devices
- 1/10 • Regulating voltage or current (G05F 1/02 takes precedence; for electric railways B60M 3/02)
- 1/12 • • wherein the variable is actually regulated by the final control device is ac (G05F 1/625 takes precedence) [4]
- 1/13 • • • using ferroresonant transformers as final control devices [4]
- 1/14 • • • using tap transformers or tap changing inductors as final control devices [4]
- 1/147 • • • • with motor driven tap switch [4]
- 1/153 • • • • controlled by discharge tubes or semiconductor devices [4]
- 1/16 • • • • combined with discharge tubes or semiconductor devices
- 1/20 • • • • • semiconductor devices only
- 1/22 • • • • combined with separate magnetic control devices having a controllable degree of saturation
- 1/24 • • • using bucking or boosting transformers as final control devices
- 1/247 • • • • with motor in control circuit [4]
- 1/253 • • • • the transformers including plural windings in series between source and load (G05F 1/247 takes precedence) [4]
- 1/26 • • • • combined with discharge tubes or semiconductor devices
- 1/30 • • • • • semiconductor devices only
- 1/32 • • • using magnetic devices having a controllable degree of saturation as final control devices
- 1/325 • • • • with specific core structure, e.g. gap, aperture, slot, permanent magnet [4]
- 1/33 • • • • with plural windings through which current to be controlled is conducted [4]
- 1/335 • • • • • on different cores [4]
- 1/34 • • • • combined with discharge tubes or semiconductor devices
- 1/38 • • • • • semiconductor devices only
- 1/40 • • • using discharge tubes or semiconductor devices as final control devices
- 1/42 • • • • discharge tubes only
- 1/44 • • • • semiconductor devices only
- 1/445 • • • • • being transistors in series with the load [3]
- 1/45 • • • • • being controlled rectifiers in series with the load [3]
- 1/455 • • • • • with phase control [3]
- 1/46 • • wherein the variable actually regulated by the final control device is dc (G05F 1/625 takes precedence) [4]
- 1/52 • • • using discharge tubes in series with the load as final control devices
- 1/54 • • • • additionally controlled by the unregulated supply
- 1/56 • • • using semiconductor devices in series with the load as final control devices
- 1/563 • • • • including two stages of regulation, at least one of which is output level responsive, e.g. coarse and fine regulation [4]
- 1/565 • • • • sensing a condition of the system or its load in addition to means responsive to deviations in the output of the system, e.g. current, voltage, power factor (G05F 1/563 takes precedence) [4]
- 1/567 • • • • • for temperature compensation [4]
- 1/569 • • • • • for protection [4]
- 1/571 • • • • • with overvoltage detector [4]
- 1/573 • • • • • with overcurrent detector [4]
- 1/575 • • • • characterised by the feedback circuit [4]
- 1/577 • • • • for plural loads [4]
- 1/585 • • • • • providing voltages of opposite polarities [4]
- 1/59 • • • • including plural semiconductor devices as final control devices for a single load [4]
- 1/595 • • • • • semiconductor devices connected in series [4]
- 1/607 • • • using discharge tubes in parallel with the load as final control devices [3]
- 1/61 • • • • including two stages of regulation, at least one of which is output level responsive [4]
- 1/613 • • • using semiconductor devices in parallel with the load as final control devices [3]
- 1/614 • • • • including two stages of regulation, at least one of which is output level responsive [4]
- 1/618 • • • using semiconductor devices in series and in parallel with the load as final control devices [4]
- 1/62 • • • using bucking or boosting dc sources
- 1/625 • • wherein it is irrelevant whether the variable actually regulated is ac or dc [4]
- 1/63 • • • using variable impedances in series with the load as final control devices [4]
- 1/635 • • • • being Hall effect devices, magnetoresistors or thermistors [4]
- 1/644 • • • • being pressure-sensitive resistors [4]
- 1/648 • • • • being plural resistors among which a selection is made [4]
- 1/652 • • • using variable impedances in parallel with the load as final control devices [4]
- 1/656 • • • using variable impedances in series and in parallel with the load as final control devices [4]
- 1/66 • Regulating electric power
- 1/67 • • to the maximum power available from a generator, e.g. from solar cell [4]
- 1/70 • Regulating power factor; Regulating reactive current or power [3]
- 3/00 Non-retroactive systems for regulating electric variables by using an uncontrolled element, or an uncontrolled combination of elements, such element or such combination having self-regulating properties**
- 3/02 • Regulating voltage or current
- 3/04 • • wherein the variable is ac
- 3/06 • • • using combinations of saturated and unsaturated inductive devices, e.g. combined with resonant circuit
- 3/08 • • wherein the variable is dc
- 3/10 • • • using uncontrolled devices with non-linear characteristics [4]
- 3/12 • • • • being glow discharge tubes
- 3/16 • • • • being semiconductor devices [3]

G05F

- 3/18 • • • • • using Zener diodes [3]
- 3/20 • • • • • using diode-transistor combinations (G05F 3/18 takes precedence) [3]
- 3/22 • • • • • wherein the transistors are of the bipolar type only (G05F 3/26, G05F 3/30 take precedence) [4]
- 3/24 • • • • • wherein the transistors are of the field-effect type only (G05F 3/26, G05F 3/30 take precedence) [4]
- 3/26 • • • • • Current mirrors [4]
- 3/28 • • • • • combined with a non-linear current amplifier [4]
- 3/30 • • • • • Regulators using the difference between the base-emitter voltages of two bipolar transistors operating at different current densities (G05F 3/26 takes precedence) [4]

5/00 Systems for regulating electric variables by detecting deviations in the electric input to the system and thereby controlling a device within the system to obtain a regulated output

- 5/02 • Phase controlled switching using electronic tubes or three or more terminal semiconductive devices [4]
- 5/04 • using a transformer or inductor as the final control device [4]
- 5/06 • • saturable [4]
- 5/08 • using a linearly acting final control device [4]

7/00 Regulating magnetic variables (details of apparatus for measuring magnetic variables involving magnetic resonance G01R 33/28) [5]

G05G CONTROL DEVICES OR SYSTEMS INsofar AS CHARACTERISED BY MECHANICAL FEATURES ONLY ("Bowden" or like mechanisms F16C 1/10; gearings or mechanisms not peculiar to this purpose F16H; speed changing or reversing mechanisms for gearings conveying rotary motion F16H 59/00-F16H 63/00)

Note(s)

1. This subclass covers:
 - members of general applicability for mechanical control;
 - mechanical systems for moving members to one or more definite settings.
2. Systems peculiar to the control of particular machines or apparatus provided for in a single other class are classified in the relevant class for such machines or apparatus, for example:
 - A61G 13/02.....Controls for adjusting operating tables
 - A61G 15/02.....Controls for adjusting operating chairs
 - A63F 13/20, A63F 13/98.....Accessories for games using an electronically generated display
 - B25J.....Manipulators, e.g. controls therefor
 - B60K 26/00.....Arrangement or mounting of propulsion-unit control devices in vehicles
 - B60T 7/00.....Vehicle brake-action initiating means
 - B62D 33/073.....Adaptations of control devices for movable vehicle cabs
 - B62K 21/00.....Cycle-steering devices
 - B62K 23/00.....Rider-operated controls specially adapted for cycles
 - B62L 3/00.....Brake-actuating mechanisms specially adapted for cycles
 - B63H 25/02.....Marine steering initiating means
 - B66B 1/00.....Controls for elevators
 - B66C 13/18.....Control systems or devices for cranes
 - B66C 13/56.....Arrangements of handles or pedals for crane operation
 - E02F 9/20.....Control devices for dredging or soil shifting machines
 - F16C 3/28.....Adjustable cranks or eccentrics
 - F16D 43/00.....Automatic clutches
 - F16K 31/00, F16K 33/00.....Controls for valves
 - F16P 3/00.....Safety devices acting in conjunction with the control or operation of a machine
 - F16P 7/02.....Stopping machines on occurrence of dangerous conditions therein
 - G02B 21/32.....Micromanipulators structurally combined with microscopes
 - G04B 1/00-G04B 18/00.....Driving mechanisms in clocks or watches
 - G06C.....Digital computers in which all the computation is effected mechanically
 - G06F 3/01.....Manual computer input arrangements
 - G06K 11/00.....Converting a pattern of mechanical parameters into electric signals
 - G21C 7/08.....Displacement of solid control elements in nuclear reactors
 - H01H.....Mechanisms for operating switch contacts
 - H03J 1/00.....Mechanical control of resonant circuits.

Subclass index

MANUALLY-ACTUATED CONTROL MECHANISMS, ONE OR MORE CONTROLLING MEMBERS	
ACTUATING ONE OR MORE CONTROLLED MEMBERS.....	7/00, 9/00, 11/00, 13/00
AUTOMATIC MOVEMENT-INITIATING DEVICES; TRIP MECHANISMS.....	15/00, 17/00
SERVO-MECHANISMS.....	19/00
PROGRAMME-CONTROL DEVICES.....	21/00
LOCKING MEANS, LIMITING MEANS; POSITIONING MEANS.....	5/00, 23/00
COMPONENT PARTS.....	1/00, 3/00, 25/00

- 1/00 Controlling members, e.g. knobs or handles; Assemblies or arrangements thereof; Indicating position of controlling members** (joysticks G05G 9/04; steering wheels for motor vehicles B62D) **[2008.04]**
- Note(s) [2008.04]**
- In this group the first place priority rule is applied, i.e. at each hierarchical level classification is made in the first appropriate place.
- 1/01 • Arrangements of two or more controlling members with respect to one another (double foot control, e.g. for instruction vehicles G05G 1/34; mounting units comprising an assembly with two or more pedals G05G 1/36) **[2008.04]**
 - 1/015 • Arrangements for indicating the position of a controlling member (means for continuously detecting pedal position G05G 1/38; means for detecting position through tactile feedback G05G 5/03) **[2008.04]**
 - 1/02 • Controlling members for hand-actuation by linear movement, e.g. push buttons **[1, 7]**
 - 1/04 • Controlling members for hand-actuation by pivoting movement, e.g. levers **[1, 7]**
 - 1/06 • • Details of their grip parts **[1, 7]**
 - 1/08 • Controlling members for hand-actuation by rotary movement, e.g. hand wheels **[1, 7]**
 - 1/10 • • Details, e.g. of discs, knobs, wheels or handles
 - 1/12 • • • Means for securing the members on rotatable spindles or the like
 - 1/30 • Controlling members actuated by foot **[2008.04]**
 - 1/32 • • with means to prevent injury **[2008.04]**
 - 1/323 • • • means disconnecting the connection between pedal and controlled member, e.g. by breaking or bending the connecting rod **[2008.04]**
 - 1/327 • • • means disconnecting the pedal from its hinge or support, e.g. by breaking or bending the support **[2008.04]**
 - 1/34 • • Double foot controls, e.g. for instruction vehicles **[2008.04]**
 - 1/36 • • Mounting units comprising an assembly of two or more pedals, e.g. for facilitating mounting **[2008.04]**
 - 1/38 • • comprising means to continuously detect pedal position **[2008.04]**
 - 1/40 • • adjustable **[2008.04]**
 - 1/405 • • • infinitely adjustable **[2008.04]**
 - 1/42 • • non-pivoting, e.g. sliding **[2008.04]**
 - 1/44 • • pivoting **[2008.04]**
 - 1/445 • • • about a central fulcrum **[2008.04]**
 - 1/46 • • Means, e.g. links, for connecting the pedal to the controlled unit **[2008.04]**
 - 1/48 • • Non-slip pedal treads; Pedal extensions or attachments characterised by mechanical features only **[2008.04]**
 - 1/483 • • • Non-slip treads **[2008.04]**
 - 1/487 • • • Pedal extensions **[2008.04]**
 - 1/50 • • Manufacturing of pedals; Pedals characterised by the material used **[2008.04]**
 - 1/52 • Controlling members specially adapted for actuation by other parts of the human body than hand or foot **[2008.04]**
 - 1/54 • Controlling members specially adapted for actuation by auxiliary operating members or extensions; Operating members or extensions therefor (pedal extensions G05G 1/487) **[2008.04]**
 - 1/56 • • Controlling members specially adapted for actuation by keys, screwdrivers or like tools **[2008.04]**
 - 1/58 • Rests or guides for relevant parts of the operator's body **[2008.04]**
 - 1/60 • • Foot rests or foot guides **[2008.04]**
 - 1/62 • • Arm rests **[2008.04]**
 - 3/00 Controlled members** (gear shifter yokes F16H 63/32); **Assemblies or arrangements thereof** (interlocking of controlled members G05G 5/08) **[1, 7]**
 - 5/00 Means for preventing, limiting or returning the movements of parts of a control mechanism, e.g. locking controlling member** (G05G 17/00 takes precedence) **[5]**
 - 5/02 • Means preventing undesired movements of a controlling member which can be moved in two or more separate steps or ways, e.g. restricting to a stepwise movement or to a particular sequence of movements (G05G 5/28 takes precedence)
 - 5/03 • Means for enhancing the operator's awareness of the arrival of the controlling member at a command or datum position; Providing feel, e.g. means for creating a counterforce (arrangements for indicating the position of the controlling member G05G 1/015) **[5, 2008.04]**
 - 5/04 • Stops for limiting movement of members, e.g. adjustable stop (G05G 5/03, G05G 5/05, G05G 5/28 take precedence) **[5]**
 - 5/05 • Means for returning or tending to return controlling members to an inoperative or neutral position, e.g. by providing return springs or resilient end-stops (G05G 5/28 takes precedence) **[5]**
 - 5/06 • for holding members in one or a limited number of definite positions only (G05G 5/03, G05G 5/05, G05G 5/28 take precedence) **[5]**
 - 5/08 • • Interlocking of members, e.g. locking a member in a particular position before or during the movement of another member
 - 5/12 • for holding members in an indefinite number of positions, e.g. by a toothed quadrant (G05G 5/28 takes precedence) **[5]**
 - 5/14 • • by locking a member with respect to a fixed quadrant, rod, or the like
 - 5/16 • • • by friction
 - 5/18 • • • by positive interengagement, e.g. by a pawl
 - 5/20 • • by locking a quadrant, rod, or the like carried by the member
 - 5/22 • • • by friction
 - 5/24 • • • by positive interengagement, e.g. by a pawl
 - 5/26 • • by other means than a quadrant, rod, or the like
 - 5/28 • for preventing unauthorised access to the controlling member or its movement to a command position **[5]**
 - 7/00 Manually-actuated control mechanisms provided with one single controlling member co-operating with one single controlled member; Details thereof** (controlling members G05G 1/00)
 - 7/02 • characterised by special provisions for conveying or converting motion, or for acting at a distance
 - 7/04 • • altering the ratio of motion or force between controlling member and controlled member as a function of the position of the controlling member
 - 7/06 • • in which repeated movement of the controlling member produces increments of movement of the controlled member (G05G 7/08 takes precedence)

- 7/08 • • in which repeated movement of the controlling member moves the controlled member through a cycle of distinct positions
- 7/10 • • specially adapted for remote control (G05G 7/04-G05G 7/08 take precedence)
- 7/12 • specially adapted for actuating a member on a system in motion with respect to the controlling member, e.g. on a rotating shaft
- 7/14 • characterised by means for delaying initiation of, or making more gradual throughout, the movement of the controlled member in response to a given input from the controlling member, e.g. by providing lost motion in the command train
- 7/16 • Special provisions for reducing the effect of slight relative movement between supports of the mechanism, e.g. resulting from resilient mounting of a controlled mechanism

- 9/00 Manually-actuated control mechanisms provided with one single controlling member co-operating with two or more controlled members, e.g. selectively, simultaneously**
- 9/02 • the controlling member being movable in different independent ways, movement in each individual way actuating one controlled member only
- 9/04 • • in which movement in two or more ways can occur simultaneously
- 9/047 • • • the controlling member being movable by hand about orthogonal axes, e.g. joysticks [5]
- 9/053 • • • • the controlling member comprising a ball [5]
- 9/06 • the controlled members being actuated successively by repeated movement of the controlling member
- 9/08 • the controlled members being actuated successively by progressive movement of the controlling member
- 9/10 • with preselection and subsequent movement of each controlled member by movement of the controlling member in two different ways, e.g. guided by a shift gate

- 11/00 Manually-actuated control mechanisms provided with two or more controlling members co-operating with one single controlled member**

- 13/00 Manually-actuated control mechanisms provided with two or more controlling members and also two or more controlled members** (interlocking G05G 5/08)
- 13/02 • with separate controlling members for preselection and shifting of controlled members

- 15/00 Mechanical devices for initiating a movement automatically due to a specific cause**
- 15/02 • due to alteration of the sense of movement of a member
- 15/04 • due to distance or angle travelled by a member
- 15/06 • due to the speed of rotation or of bodily movement of a member, e.g. passing an upper or lower limit thereof (speedometers G01P)
- 15/08 • due to the load or torque on a member, e.g. if exceeding a predetermined value thereof

- 17/00 Mechanical devices for moving a member after being released; Trip or release mechanisms characterised thereby**

- 19/00 Servo-mechanisms with follow-up action, e.g. occurring in steps**

- 21/00 Mechanical apparatus for control of a series of operations, i.e. programme control, e.g. involving a set of cams** (G05G 5/02 takes precedence)

- 23/00 Means for ensuring the correct positioning of parts of control mechanisms, e.g. for taking-up play**
- 23/02 • self-adjusting

- 25/00 Other details, features or accessories of control mechanisms, e.g. supporting intermediate members elastically**
- 25/02 • Inhibiting the generation or transmission of noise [5]
- 25/04 • Sealing against entry of dust, weather or the like [5]