

SECTION G — PHYSICS

G01 MEASURING; TESTING

G01B MEASURING LENGTH, THICKNESS OR SIMILAR LINEAR DIMENSIONS; MEASURING ANGLES; MEASURING AREAS; MEASURING IRREGULARITIES OF SURFACES OR CONTOURS

Note(s) [4]

1. This subclass covers measuring of position or displacement in terms of linear or angular dimensions.
2. In this subclass, the groups are distinguished by the means of measurement which is of major importance. Thus the mere application of other means for giving a final indication does not affect the classification.
3. Attention is drawn to the Notes following the title of class G01.
4. Machines operated on similar principles to the hand-held devices specified in this subclass are classified with these devices.
5. Measuring arrangements or details thereof covered by two or more of groups G01B 3/00-G01B 17/00 are classified in group G01B 21/00 if no single other group can be selected as being predominantly applicable.

Subclass index

MEASURING DEVICES CHARACTERISED BY THE MATERIAL.....	1/00
PREDOMINANT METHODS USED IN MEASURING DEVICES	
Mechanical.....	3/00, 5/00
Electric or magnetic.....	7/00
By fluids.....	13/00
By light waves; by other electro-magnetic waves or radiation.....	9/00, 11/00, 15/00
By sonic waves.....	17/00
OTHER MEASURING ARRANGEMENTS.....	21/00

1/00	Measuring instruments characterised by the selection of material therefor [1, 2006.01]	3/30	• Bars, blocks, or strips in which the distance between a pair of faces is fixed, although it may be preadjustable, e.g. end measure, feeler strip [1, 2006.01]
3/00	Instruments as specified in the subgroups and characterised by the use of mechanical measuring means (arrangements for measuring particular parameters G01B 5/00; devices of general interest specially adapted or mounted for storing and repeatedly paying-out and re-storing lengths of material B65H 75/34) [1, 2, 2006.01]	3/32	• • Holders therefor [1, 2006.01]
		3/34	• Ring or other apertured gauges, e.g. "go/no-go" gauge [1, 2006.01]
		3/36	• • for external screw threads [1, 2006.01]
3/02	• Rulers or tapes with scales or marks for direct reading [1, 2006.01]	3/38	• Gauges with an open yoke and opposed faces, i.e. calipers, in which the internal distance between the faces is fixed, although it may be preadjustable [1, 2006.01]
3/04	• • rigid [1, 2006.01]	3/40	• • for external screw threads [1, 2006.01]
3/06	• • • folding [1, 2006.01]	3/42	• • of limit-gauge type, i.e. "go/no-go" (G01B 3/40 takes precedence) [1, 2006.01]
3/08	• • • extensible [1, 2006.01]	3/44	• • • preadjustable for wear or tolerance [1, 2006.01]
3/10	• • flexible [1, 2006.01]	3/46	• Plug gauges for internal dimensions with engaging surfaces which are at a fixed distance, although they may be preadjustable [1, 2006.01]
3/11	• Chains for measuring length [1, 2006.01]	3/48	• • for internal screw threads [1, 2006.01]
3/12	• Measuring wheels [1, 2006.01]	3/50	• • of limit-gauge type, i.e. "go/no-go" (G01B 3/48 takes precedence) [1, 2006.01]
3/14	• Templates for checking contours [1, 2006.01]	3/52	• • • preadjustable for wear or tolerance [1, 2006.01]
3/16	• Compasses, i.e. with a pair of pivoted arms [1, 2006.01]	3/56	• Gauges for measuring angles or tapers, e.g. conical calipers [1, 2006.01]
3/18	• Micrometers [1, 2006.01]	5/00	Measuring arrangements characterised by the use of mechanical means (instruments of the types covered by group G01B 3/00 <i>per se</i> G01B 3/00) [1, 2, 2006.01]
3/20	• Slide gauges [1, 2006.01]	5/004	• for measuring coordinates of points [6, 2006.01]
3/22	• Feeler-pin gauges, e.g. dial gauges (for measuring contours or curvatures G01B 5/20) [1, 2006.01]		
3/24	• • with open yoke, i.e. calipers [1, 2006.01]		
3/26	• • Plug gauges [1, 2006.01]		
3/28	• • Depth gauges [1, 2006.01]		

- 5/008 • • using coordinate measuring machines [6, 2006.01]
- 5/012 • • • Contact-making feeler heads therefor [6, 2006.01]
- 5/016 • • • • Constructional details of contacts [6, 2006.01]
- 5/02 • for measuring length, width, or thickness (G01B 5/004, G01B 5/08 take precedence) [1, 6, 2006.01]
- 5/04 • • specially adapted for measuring length or width of objects while moving [1, 2006.01]
- 5/06 • • for measuring thickness [1, 2006.01]
- 5/08 • for measuring diameters [1, 2006.01]
- 5/10 • • of objects while moving [1, 2006.01]
- 5/12 • • internal diameters [1, 2006.01]
- 5/14 • for measuring distance or clearance between spaced objects or spaced apertures (G01B 5/24 takes precedence) [1, 2006.01]
- 5/16 • • between a succession of regularly spaced objects or regularly spaced apertures [1, 2006.01]
- 5/18 • for measuring depth [1, 2006.01]
- 5/20 • for measuring contours or curvatures [1, 2006.01]
- 5/207 • • using a plurality of fixed, simultaneously operating transducers (G01B 5/213-G01B 5/22 take precedence) [6, 2006.01]
- 5/213 • • for measuring radius of curvature [6, 2006.01]
- 5/22 • • Spherometers [1, 2006.01]
- 5/24 • for measuring angles or tapers; for testing the alignment of axes [1, 2006.01]
- 5/245 • • for testing perpendicularity [6, 2006.01]
- 5/25 • • for testing the alignment of axes [1, 2006.01]
- 5/252 • • • for measuring eccentricity, i.e. lateral shift between two parallel axes [6, 2006.01]
- 5/255 • • for testing wheel alignment [1, 2006.01]
- 5/26 • for measuring areas, e.g. planimeter (integrators in general G06G) [1, 2006.01]
- 5/28 • for measuring roughness or irregularity of surfaces [1, 2006.01]
- 5/30 • for measuring the deformation in a solid, e.g. mechanical strain gauge [1, 2006.01]
- 7/00 Measuring arrangements characterised by the use of electric or magnetic means [1, 2006.01]**
- 7/004 • for measuring coordinates of points [6, 2006.01]
- 7/008 • • using coordinate measuring machines [6, 2006.01]
- 7/012 • • • Contact-making feeler heads therefor [6, 2006.01]
- 7/016 • • • • Constructional details of contacts [6, 2006.01]
- 7/02 • for measuring length, width, or thickness (G01B 7/004, G01B 7/12 takes precedence) [1, 6, 2006.01]
- 7/04 • • specially adapted for measuring length or width of objects while moving [1, 2006.01]
- 7/06 • • for measuring thickness [1, 2006.01]
- 7/12 • for measuring diameters [1, 2006.01]
- 7/13 • • Internal diameters [6, 2006.01]
- 7/14 • for measuring distance or clearance between spaced objects or spaced apertures (G01B 7/30 takes precedence) [1, 2006.01]
- 7/15 • • being regularly spaced [6, 2006.01]
- 7/16 • for measuring the deformation in a solid, e.g. by resistance strain gauge [1, 2006.01]
- 7/24 • • using change in magnetic properties [1, 2006.01]
- 7/26 • for measuring depth [1, 2006.01]
- 7/28 • for measuring contours or curvatures [1, 2006.01]

- 7/287 • • using a plurality of fixed, simultaneously operating transducers (G01B 7/293 takes precedence) [6, 2006.01]
- 7/293 • • for measuring radius of curvature [6, 2006.01]
- 7/30 • for measuring angles or tapers; for testing the alignment of axes [1, 2006.01]
- 7/305 • • for testing perpendicularity [6, 2006.01]
- 7/31 • • for testing the alignment of axes [1, 2006.01]
- 7/312 • • • for measuring eccentricity, i.e. lateral shift between two parallel axes [6, 2006.01]
- 7/315 • • for testing wheel alignment [1, 2006.01]
- 7/32 • for measuring areas (integrators in general G06G) [1, 2006.01]
- 7/34 • for measuring roughness or irregularity of surfaces [1, 2006.01]
- 9/00 Instruments as specified in the subgroups and characterised by the use of optical measuring means (arrangements for measuring particular parameters G01B 11/00) [1, 2, 2006.01]**
- 9/02 • Interferometers [1, 2006.01]
- 9/021 • • using holographic techniques [2, 2006.01]
- 9/023 • • • for contour producing (G01B 9/025-G01B 9/029 take precedence) [2, 2006.01]
- 9/025 • • • Double-exposure technique [2, 2006.01]
- 9/027 • • • in real time [2, 2006.01]
- 9/029 • • • by time averaging [2, 2006.01]
- 9/04 • Measuring microscopes [1, 2006.01]
- 9/06 • Measuring telescopes [1, 2006.01]
- 9/08 • Optical projection comparators [1, 2006.01]
- 9/10 • Goniometers for measuring angles between surfaces [1, 2006.01]
- 11/00 Measuring arrangements characterised by the use of optical means (instruments of the types covered by group G01B 9/00 per se G01B 9/00) [1, 2, 2006.01]**
- 11/02 • for measuring length, width, or thickness (G01B 11/08 takes precedence) [1, 2006.01]
- 11/03 • • by measuring coordinates of points [3, 2006.01]
- 11/04 • • specially adapted for measuring length or width of objects while moving [1, 2006.01]
- 11/06 • • for measuring thickness [1, 2006.01]
- 11/08 • for measuring diameters [1, 2006.01]
- 11/10 • • of objects while moving [1, 2006.01]
- 11/12 • • internal diameters [1, 2006.01]
- 11/14 • for measuring distance or clearance between spaced objects or spaced apertures (G01B 11/26 takes precedence; rangefinders G01C 3/00) [1, 2006.01]
- 11/16 • for measuring the deformation in a solid, e.g. optical strain gauge [1, 2006.01]
- 11/22 • for measuring depth [1, 2006.01]
- 11/24 • for measuring contours or curvatures [1, 2006.01]
- 11/245 • • using a plurality of fixed, simultaneously operating transducers (G01B 11/255 takes precedence) [7, 2006.01]
- 11/25 • • by projecting a pattern, e.g. moiré fringes, on the object (G01B 11/255 takes precedence) [7, 2006.01]
- 11/255 • • for measuring radius of curvature [7, 2006.01]
- 11/26 • for measuring angles or tapers; for testing the alignment of axes [1, 2006.01]
- 11/27 • • for testing the alignment of axes [1, 2006.01]
- 11/275 • • for testing wheel alignment [1, 2006.01]
- 11/28 • for measuring areas (integrators in general G06G) [1, 2006.01]

- 11/30 • for measuring roughness or irregularity of surfaces [1, 2006.01]

13/00 Measuring arrangements characterised by the use of fluids [1, 2006.01]

- 13/02 • for measuring length, width, or thickness (G01B 13/08 takes precedence) [1, 2006.01]
- 13/03 • • by measuring coordinates of points [3, 2006.01]
- 13/04 • • specially adapted for measuring length or width of objects while moving [1, 2006.01]
- 13/06 • • for measuring thickness [1, 2006.01]
- 13/08 • for measuring diameters [1, 2006.01]
- 13/10 • • internal diameters [1, 2006.01]
- 13/12 • for measuring distance or clearance between spaced objects or spaced apertures (G01B 13/18 takes precedence) [1, 2006.01]
- 13/14 • for measuring depth [1, 2006.01]
- 13/16 • for measuring contours or curvatures [1, 2006.01]
- 13/18 • for measuring angles or tapers; for testing the alignment of axes [1, 2006.01]
- 13/19 • • for testing the alignment of axes [1, 2006.01]
- 13/195 • • for testing wheel alignment [1, 2006.01]
- 13/20 • for measuring areas, e.g. pneumatic planimeter (integrators in general G06G) [1, 2006.01]
- 13/22 • for measuring roughness or irregularity of surfaces [1, 2006.01]
- 13/24 • for measuring the deformation in a solid [3, 2006.01]

15/00 Measuring arrangements characterised by the use of wave or particle radiation (G01B 9/00, G01B 11/00 take precedence) [1, 4, 2006.01]

- 15/02 • for measuring thickness [1, 2006.01]
- 15/04 • for measuring contours or curvatures [1, 2006.01]
- 15/06 • for measuring the deformation in a solid [1, 2006.01]
- 15/08 • for measuring roughness or irregularity of surfaces [6, 2006.01]

17/00 Measuring arrangements characterised by the use of infrasonic, sonic, or ultrasonic vibrations [1, 4, 2006.01]

- 17/02 • for measuring thickness [1, 2006.01]
- 17/04 • for measuring the deformation in a solid, e.g. by vibrating string [1, 2006.01]
- 17/06 • for measuring contours or curvatures [6, 2006.01]
- 17/08 • for measuring roughness or irregularity of surfaces [6, 2006.01]

21/00 Measuring arrangements or details thereof in so far as they are not adapted to particular types of measuring means of the other groups of this subclass [3, 2006.01]

- 21/02 • for measuring length, width, or thickness (G01B 21/10 takes precedence) [3, 2006.01]
- 21/04 • • by measuring coordinates of points [3, 2006.01]
- 21/06 • • specially adapted for measuring length or width of objects while moving [3, 2006.01]
- 21/08 • • for measuring thickness [3, 2006.01]
- 21/10 • for measuring diameters [3, 2006.01]
- 21/12 • • of objects while moving [3, 2006.01]
- 21/14 • • internal diameters [3, 2006.01]
- 21/16 • for measuring distance or clearance between spaced objects [3, 2006.01]
- 21/18 • for measuring depth [3, 2006.01]
- 21/20 • for measuring contours or curvatures, e.g. determining profile [3, 2006.01]
- 21/22 • for measuring angles or tapers; for testing the alignment of axes [3, 2006.01]
- 21/24 • • for testing the alignment of axes [3, 2006.01]
- 21/26 • • for testing wheel alignment [3, 2006.01]
- 21/28 • for measuring areas (integrators in general G06G) [3, 2006.01]
- 21/30 • for measuring roughness or irregularity of surfaces [3, 2006.01]
- 21/32 • for measuring the deformation in a solid [3, 2006.01]